

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 05.14.2019 Page 14.2019

**Revision date:** 02.08.2024

**Clean Fast** 

#### **SECTION 1: Identification**

**Product Identifier** 

**Product Name:** Clean Fast **Product code:** C-1006

#### **Recommended Use of the Product and Restriction on Use**

Relevant Identified Uses: Presoak, Friction Lubricator

**Uses Advised Against: NA** 

**Reasons Why Uses Advised Against:** Not determined or not applicable.

#### **Manufacturer or Supplier Details**

Manufacturer: United States

Heiden Industries 1200 Veterans Blvd. Kenner, LA. 70062 8008784913 TODD@HEIDENIND.COM

# **Emergency Telephone Number:**

**North America** 

CHEMTREC 800-424-9300 (24 hours)

#### SECTION 2: Hazard(s) Identification

# **GHS Classification:**

Skin corrosion, category 1A
Serious eye damage, category 1
Carcinogenicity, category 2
Specific target organ toxicity - repeated exposure, category 2

### **Label elements**

#### **Hazard Pictograms:**





# **Signal Word:** Danger **Hazard statements:**

H314 Causes severe skin burns and eye damage

H318 Causes serious eye damage

H351 Suspected of causing cancer.

H373 May cause damage to organs.

# **Precautionary Statements:**

Page 1 of 21

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 05.14.2019

**Revision date: 02.08.2024** 

#### **Clean Fast**

P260 Do not breathe dust/fume/gas/mist/vapors/spray

P264 Wash contaminated area thoroughly after handling.

P280 Wear protective gloves/protective clothing/eye protection/face protection

P202 Do not handle until all safety precautions have been read and understood

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

P363 Wash contaminated clothing before reuse

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P314 Get medical advice/attention if you feel unwell

P405 Store locked up

P501 It is the responsibility of the waste generator to characterize all waste materials according to applicable regulatory entities.

Hazards Not Otherwise Classified: None

# **SECTION 3: Composition/Information on Ingredients**

Identification	Name	Weight %
CAS Number: 68515-73-1	D-Glucopyranose, oligomers, decyl octyl glycosides	1-40
CAS Number: 1310-73-2	Sodium hydroxide	1-30
CAS Number: 527-07-1	Sodium gluconate	1-20
CAS Number: 7758-29-4	Pentasodium triphosphate	0.94-20
CAS Number: 1300-72-7	Sodium Xylenesulfonate	<15
CAS Number: 5064-31-3	Trisodium nitrilotriacetate	<0.4
CAS Number: 111-76-2	2-Butoxyethanol	<10
CAS Number: 61789-40-0	1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-, N-coco acyl derivs., hydroxides, inner salts	<5
CAS Number: 9004-82-4	2-dodecoxyethyl hydrogen sulfate	1-10
CAS Number: 68131-39-5	Alcohols, C12-15, ethoxylated	1-5
CAS Number: 50-00-0	Formaldehyde	<0.0225
CAS Number: 79-43-6	Dichloroacetic acid	<0.0225

Page 2 of 21

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

**Initial Preparation Date: 05.14.2019** 

**Revision date: 02.08.2024** 

#### **Clean Fast**

CAS Number: 75-21-8	Ethylene oxide	<0.009
CAS Number: 123-91-1	1,4-dioxane	<0.009
CAS Number: 107-21-1	Ethane-1,2-diol	<0.0072

Additional Information: None

#### **SECTION 4: First Aid Measures**

#### **Description of First Aid Measures**

#### **General Notes:**

Show this Safety Data Sheet to attending Medical Professional.

#### **After Inhalation:**

If inhaled, remove person to fresh air and place in a position comfortable for breathing. Keep person at rest. If breathing is difficult, administer oxygen. If breathing has stopped, provide artificial respiration. If symptoms develop or persist, seek medical advice/attention.

If inhaled, remove person to fresh air and place in a position comfortable for breathing. Keep person at rest. If breathing is difficult, administer oxygen. If breathing has stopped, provide artificial respiration. If experiencing respiratory symptoms, seek medical advice/attention.

#### After Skin Contact:

Treatment is urgent. Seek emergency medical treatment. Remove contaminated clothing and shoes. Rinse skin with copious amounts of water [shower] for several minutes. Launder contaminated clothing

Remove contaminated clothing and shoes. Rinse skin with copious amounts of water [shower] for several minutes. Launder contaminated clothing before reuse. If symptoms develop or persist, seek medical advice/attention.

#### **After Eye Contact:**

Immediately rinse eyes with plenty of gently flowing lukewarm water for 15 minutes. Remove contact lenses if present and easy to do so. Protect unexposed eye. Seek immediate medical attention, preferably from an ophthalmologist.

Rinse eyes with plenty of water for several minutes. Remove contact lenses if present and easy to do so. Protect unexposed eye. If symptoms develop or persist, seek medical advice/attention.

#### **After Swallowing:**

If Swallowed, DO NOT induce vomiting unless directed otherwise by a medical professional. Rinse mouth with water. Never give anything to an unconscious person. Seek medical attention.

If swallowed, DO NOT induce vomiting unless told to do so by a physician or poison control center. Rinse mouth with water. Never give anything by mouth to an unconscious person. If spontaneous vomiting occurs, place on the left side with head down to prevent aspiration of liquid into the lungs. Seek immediate medical attention.

If swallowed, DO NOT induce vomiting unless told to do so by a physician or poison control center. Rinse mouth with water. Never give anything by mouth to an unconscious person. If spontaneous vomiting occurs, place on the left side with head down to prevent aspiration of liquid into the lungs. If symptoms develop or persist, seek medical advice/attention.

# Most Important Symptoms and Effects, Both Acute and Delayed

#### **Acute Symptoms and Effects:**

Exposure to skin may result in redness, pain, burning, inflammation and tissue damage. Exposure to

Page 3 of 21

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 05.14.2019

**Revision date: 02.08.2024** 

#### **Clean Fast**

eyes may result in irritation, redness, pain, inflammation, itching, burning, tearing, corneal damage and loss of vision. Exposure via inhalation may result in cough, sore throat, burning sensation and shortness of breath. Exposure via ingestion may result in burns of the mouth and throat, abdominal pain, burning sensation in the throat and chest, nausea, vomiting, shock or collapse.

Eye contact may result in irritation, redness, pain, inflammation, itching, burning, tearing, corneal damage and loss of vision.

#### **Delayed Symptoms and Effects:**

Effects are dependent on exposure (dose, concentration, contact time).

Suspected of causing cancer. Effects are dependent on exposure (dose, concentration, contact time).

May cause damage to organs through prolonged or repeated exposure. Effects are dependent on exposure (dose, concentration, contact time).

# **Immediate Medical Attention and Special Treatment**

#### **Specific Treatment:**

In case of eye contact, seek prompt medical attention while rinsing is continued.

In case of skin contact, seek prompt medical attention while rinsing is continued.

In case of ingestion, seek prompt medical attention.

#### **Notes for the Doctor:**

Not determined or not applicable.

#### **SECTION 5: Firefighting Measures**

#### **Extinguishing Media**

#### **Suitable Extinguishing Media:**

Water mist/fog, carbon dioxide, dry chemical or alcohol resistant foam.

#### **Unsuitable Extinguishing Media:**

Do not use water jet.

#### **Specific Hazards During Fire-Fighting:**

Thermal decomposition may produce irritating/toxic fumes/gases.

#### **Special Protective Equipment for Firefighters:**

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full-face piece operated in positive pressure mode.

#### **Special precautions:**

Avoid contact with skin, eyes, hair and clothing. Do not breathe fumes/gas/mists/aerosols/vapors/dusts. Move containers from fire area if safe to do so. Use water spray/fog for cooling fire exposed containers. Avoid unnecessary run-off of extinguishing media which may cause pollution.

#### **SECTION 6: Accidental Release Measures**

#### Personal Precautions, Protective Equipment, and Emergency Procedures:

Evacuate unnecessary personnel. Ventilate area. Extinguish any sources of ignition. Wear recommended personal protective equipment (see Section 8). Avoid contact with skin, eyes and clothing. Avoid breathing mist, vapor, dust, fume and spray. Do not walk through spilled material. Wash thoroughly after handling. Evacuate unnecessary personnel. Ventilate area. Extinguish any sources of ignition. Wear recommended personal protective equipment (see Section 8). Do not get on skin, eyes or on clothing. Avoid breathing mist, vapor, dust, fume and spray. Do not walk through spilled material. Wash thoroughly after handling. Remove contaminated clothing and launder before reuse.

#### **Environmental Precautions:**

Prevent further leakage or spillage if safe to do so. Prevent from reaching drains, sewers and waterways.

Page 4 of 21

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

**Initial Preparation Date:** 05.14.2019 Page 5 of 21

**Revision date: 02.08.2024** 

**Clean Fast** 

Discharge into the environment must be avoided.

### Methods and Material for Containment and Cleaning Up:

Do not touch damaged containers or spilled material unless wearing appropriate personal protective clothing. Stop leak if you can do it without risk. Contain and collect spillage and place in suitable container for future disposal. Dispose of in accordance with all applicable regulations (see Section 13).

Do not touch damaged containers or spilled material unless wearing appropriate personal protective clothing. Avoid breathing dust, mist, fumes, vapors or spray. Stop leak if you can do it without risk. Contain and collect spillage and place in suitable container for future disposal. Dispose of in accordance with all applicable regulations (see Section 13).

#### **Reference to Other Sections:**

For personal protective equipment see Section 8. For disposal see Section 13.

#### **SECTION 7: Handling and Storage**

#### **Precautions for Safe Handling:**

Use appropriate personal protective equipment (see Section 8). Prevent skin contact. Do not get in eyes. Use only with adequate ventilation. Do not add water to the corrosive product. If it is necessary to mix a corrosive product with water, do so slowly adding the corrosive to cold water, in small amounts, and stir frequently. Avoid breathing mist/vapor/spray/dust. Do not eat, drink, smoke, or use personal products when handling chemical substances. Wash affected areas thoroughly after handling. Keep away from incompatible materials (See Section 10). Keep containers tightly closed when not in use. Keep only in original packaging. Use appropriate personal protective equipment (see Section 8). Use only with adequate ventilation. Avoid breathing mist/vapor/spray/dust. Do not eat, drink, smoke, or use personal products when handling chemical substances. Do not get in eyes. Avoid contact with skin and clothing. Wash affected areas thoroughly after handling. Keep away from incompatible materials (See Section 10). Keep containers tightly closed when not in use.

Use appropriate personal protective equipment (see Section 8). Use only with adequate ventilation. Avoid breathing mist/vapor/spray/dust. Do not eat, drink, smoke, or use personal products when handling chemical substances. Avoid contact with skin, eyes and clothing. Wash affected areas thoroughly after handling. Keep away from incompatible materials (See Section 10). Keep containers tightly closed when not

#### Conditions for Safe Storage, Including Any Incompatibilities:

Store in cool, dry, well-ventilated location out of direct sunlight and away from exit paths. Store in a corrosion-resistant container with a resistant inner liner. Inspect containers and storage area regularly for signs of leak and damage. Store containers at a convenient height for handling, below eye level if possible. High shelving increases the risk of dropping containers, personal injury and exposure. Ensure that appropriate fire fighting and spill-clean up equipment is readily available. Keep away from food and beverages. Protect from freezing and physical damage. Store away from heat, open flames and other sources of ignition. Store separately. Keep container tightly sealed. Store away from incompatible materials (See Section 10).

Store in cool, dry, well-ventilated location out of direct sunlight. Keep away from food and beverages. Protect from freezing and physical damage. Store away from heat, open flames and other sources of ignition. Keep container tightly sealed. Store away from incompatible materials (See Section 10). Store in cool and dry location and out of direct sunlight. Store away from sources of heat or ignition. Store away from incompatible materials described in Section 10. Keep containers closed when not in use. Keep away from food and beverages. Protect from freezing and physical damage.

#### **SECTION 8: Exposure Controls/Personal Protection**

Only those substances with limit values have been included below.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

**Initial Preparation Date:** 05.14.2019

**Revision date:** 02.08.2024

**Clean Fast** 

### **Occupational Exposure Limit Values:**

Country (Legal Basis)	Substance	Identifier	Permissible concentration
ACGIH	Sodium hydroxide	1310-73-2	Ceiling Limit: 2 mg/m³
	2-Butoxyethanol	111-76-2	8-Hour TWA: 20 ppm
	Ethane-1,2-diol	107-21-1	8-Hour TWA: 25 ppm (vapor fraction)
	Ethane-1,2-diol	107-21-1	15-Minute STEL: 50 ppm (vapor fraction)
	Ethane-1,2-diol	107-21-1	15-Minute STEL: 10 mg/m³ (aerosol only, inhalable fraction)
	Ethylene oxide	75-21-8	8-Hour TWA: 1 ppm
	Dichloroacetic acid	79-43-6	8-Hour TWA: 0.5 ppm
	Formaldehyde	50-00-0	15-Minute STEL: 0.3 ppm
	Formaldehyde	50-00-0	TLV-TWA: 0.1 ppm (8 hr)
	1,4-dioxane	123-91-1	8-Hour TWA: 20 ppm
OSHA	Sodium hydroxide	1310-73-2	8-Hour TWA-PEL: 2 mg/m <sup>3</sup>
	2-Butoxyethanol	111-76-2	8-Hour TWA-PEL: 240 mg/m <sup>3</sup> (50 ppm)
	Ethylene oxide	75-21-8	8-Hour TWA-PEL: 1 ppm
	Ethylene oxide	75-21-8	15-Minute STEL: 5 ppm
	Ethylene oxide	75-21-8	8-Hour TWA: 0.5 ppm (Action level)
	Formaldehyde	50-00-0	STEL: 2 ppm
	Formaldehyde	50-00-0	TWA: 0.75 ppm
	1,4-dioxane	123-91-1	8-Hour TWA-PEL: 360 mg/m <sup>3</sup> (100 ppm)
NIOSH	Sodium hydroxide	1310-73-2	IDLH: 10 mg/m <sup>3</sup>
	2-Butoxyethanol	111-76-2	IDLH: 700 ppm
	2-Butoxyethanol	111-76-2	REL-TWA: 24 mg/m³ (5 ppm [up to 10 hr])
	Sodium hydroxide	1310-73-2	Ceiling Limit: 2 mg/m³
	Ethylene oxide	75-21-8	IDLH: 800 ppm
	Ethylene oxide	75-21-8	Ceiling Limit: 9 mg/m³ (5 ppm [10-min/day])
	Ethylene oxide	75-21-8	REL-TWA: 0.18 mg/m³ (0.1 ppm [up to 10 hr])
	Formaldehyde	50-00-0	IDLH: 20 ppm
	Formaldehyde	50-00-0	Ceiling Limit: 0.1 ppm ([15-min])
	Formaldehyde	50-00-0	REL: 0.016 ppm ([for up to a 10-hour workday)
	1,4-dioxane	123-91-1	IDLH: 500 ppm
	1,4-dioxane	123-91-1	Ceiling Limit: 3.6 mg/m³ (1 ppm [30-min])
United States(California)	Sodium hydroxide	1310-73-2	Ceiling Limit: 2 mg/m³
	Sodium hydroxide	1310-73-2	REL: 8 ug/m³ (Acute Inhalation)

Page 6 of 21

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

**Initial Preparation Date:** 05.14.2019

**Revision date: 02.08.2024** 

**Clean Fast** 

Country (Legal Basis)	Substance	Identifier	Permissible concentration
	2-Butoxyethanol	111-76-2	8-Hour TWA-PEL: 97 mg/m <sup>3</sup> (20 ppm)
	Ethylene oxide	75-21-8	15-Minute STEL: 5 ppm
	Ethylene oxide	75-21-8	8-Hour TWA-PEL: 2 mg/m³ (1 ppm)
	Ethylene oxide	75-21-8	8-Hour TWA: 0.5 ppm (Action level)
	Formaldehyde	50-00-0	15-Minute STEL: 2 ppm
	Formaldehyde	50-00-0	8-Hour TWA-PEL: 0.75 ppm
	Formaldehyde	50-00-0	REL: 55 ug/m³ (Acute Inhalation)
	Formaldehyde	50-00-0	REL: 9 ug/m³ (Chronic Inhalation)
	Ethane-1,2-diol	107-21-1	Ceiling Limit: 100 mg/m³ (40 ppm)
	1,4-dioxane	123-91-1	8-Hour TWA-PEL: 1 mg/m <sup>3</sup> (0.28 ppm)
United States	2-Butoxyethanol	111-76-2	8-Hour TWA: 120 mg/m³ (25 ppm [U.S. State, Tennessee])

# **Biological Limit Values:**

Country (Legal Basis)	Substance	Identifi er	Determinant	Specimen	Sampling time	Permissible limits
ACGIH	2-Butoxyethanol	111-76- 2	Butoxyacetic acid (with hydrolysis)	Creatinine in Urine	End of shift	200 mg/g
	Ethylene oxide	75-21-8	N-(2- hydroxyethyl)- valine (HEV) hemoglobin adducts	Hemoglobin adducts	Not critical	5000 pmol/g
	Ethylene oxide	75-21-8	1. '	Creatinine in urine	End of shift	5 μg/g

#### **Information on Monitoring Procedures:**

Not determined or not applicable.

#### **Appropriate Engineering Controls:**

Emergency eye wash stations and safety showers should be available in the immediate vicinity of use or handling. Provide adequate ventilation to maintain the airborne concentrations of vapor, mists, and/or dusts below the applicable workplace exposure limits, while observing recognized national standards (or equivalent).

# **Personal Protection Equipment**

#### **Eye and Face Protection:**

Use safety glasses with side shields or goggles. Consider the use of a face shield for splash protection. Use eye protection equipment that has been tested and approved by recognized national standards (or equivalent).

Safety glasses or goggles. Use eye protection equipment that has been tested and approved by recognized national standards (or equivalent).

# **Skin and Body Protection:**

Chemical resistant, impervious gloves approved by the appropriate standards. Gloves must be inspected

Page 7 of 21

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 05.14.2019

**Revision date: 02.08.2024** 

#### **Clean Fast**

prior to use. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. Avoid skin contact with used gloves. Appropriate techniques should be used to remove used gloves and contaminated clothing. Full body protection should be worn. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Ensure that all personal protective equipment is approved by recognized national standards (or equivalent).

Chemical resistant, impervious gloves approved by the appropriate standards. Gloves must be inspected prior to use. Avoid skin contact with used gloves. Appropriate techniques should be used to remove used gloves and contaminated clothing. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Ensure that all personal protective equipment is approved by recognized national standards (or equivalent).

#### **Respiratory Protection:**

If engineering controls do not maintain airborne concentrations below the applicable workplace exposure limits, or to an acceptable level (if exposure limits have not been established), a respirator approved by recognized national standards (or equivalent) must be worn.

If engineering controls do not maintain airborne concentrations below the applicable workplace exposure limits, or to an acceptable level (if exposure limits have not been established), a respirator approved by recognized national standards (or equivalent) must be worn. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.

#### **General Hygienic Measures:**

When handling chemical products, do not eat, drink or smoke. Wash hands after handling, before breaks, and at the end of the workday. Avoid contact with skin, eyes and clothing. Wash contaminated clothing before reuse. Perform routine housekeeping.

#### **SECTION 9: Physical and Chemical Properties**

#### Information on Basic Physical and Chemical Properties

Appearance	Liquid
Odor	Std.
Odor threshold	Not determined or not available.
рН	14
Melting point/freezing point	Not determined or not available.
Initial boiling point/range	Not determined or not available.
Flash point (closed cup)	Not determined or not available.
Evaporation rate	Not determined or not available.
Flammability (solid, gas)	Not determined or not available.
Upper flammability/explosive limit	Not determined or not available.
Lower flammability/explosive limit	Not determined or not available.
Vapor pressure	Not determined or not available.
Vapor density	Not determined or not available.
Density	Not determined or not available.
Relative density	Not determined or not available.

Page 8 of 21

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 05.14.2019

**Revision date: 02.08.2024** 

#### **Clean Fast**

Solubilities	Not determined or not available.
Partition coefficient (n-octanol/water)	Not determined or not available.
Auto/Self-ignition temperature	Not determined or not available.
Decomposition temperature	Not determined or not available.
Dynamic viscosity	Not determined or not available.
Kinematic viscosity	Not determined or not available.
Explosive properties	Not determined or not available.
Oxidizing properties	Not determined or not available.

# **SECTION 10: Stability and Reactivity**

# **Reactivity:**

Not reactive under recommended handling and storage conditions.

#### **Chemical Stability:**

Stable under recommended handling and storage conditions.

# **Possibility of Hazardous Reactions:**

Hazardous reactions are not anticipated under recommended conditions of handling and storage.

#### **Conditions to Avoid:**

Avoid generation of aerosols and mists, extreme heat, open flames, hot surfaces, sparks, ignition sources and incompatible materials.

Extreme heat, open flames, hot surfaces, sparks, ignition sources and incompatible materials.

#### **Incompatible Materials:**

None known.

#### **Hazardous Decomposition Products:**

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

# **SECTION 11: Toxicological Information**

#### **Acute Toxicity**

**Assessment:** Based on available data, the classification criteria are not met.

Product Data: No data available.

#### **Substance Data:**

Name	Route	Result
2-Butoxyethanol	Dermal ATE	LD50 Rabbit: 1100 mg/kg
	Oral ATE	LD50 Rat: 1200 mg/kg
	Inhalation ATE	LC50 Rat: 3 mg/L (4 hr [Vapours])
Trisodium nitrilotriacetate	oral	LD50 Rat: 1100 mg/kg
	dermal	LD50 Rabbit: >2000 mg/kg
	inhalation	LC50 Rat: >5 mg/L (4 hr - Aerosol)
Sodium hydroxide	Oral ATE	LD50 Rat: 500 mg/kg
	dermal	LD50 Rabbit: 1350 mg/kg
D-Glucopyranose, oligomers,	oral	LD50 Rat: > 2000 mg/kg
decyl octyl glycosides	dermal	LD50 Rabbit: > 2000 mg/kg
2-dodecoxyethyl hydrogen sulfate	oral	LD50 Rat: 500 mg/kg

Page 9 of 21

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 05.14.2019 Page 10 of 21

**Revision date:** 02.08.2024

# **Clean Fast**

Name	Route	Result
Alcohols, C12-15, ethoxylated	oral	LD50 Rat: > 2000 mg/kg
1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-,	oral	LD50 Rat: > 5000 mg/kg
N-coco acyl derivs., hydroxides, inner salts	dermal	LD50 Rat: > 2000 mg/kg
Ethane-1,2-diol	dermal	LD50 Mouse: > 3500 mg/kg
	Oral ATE	LD50 Rat: 500 mg/kg (Converted acute toxicity point estimate)
	inhalation	LC50 Rat: >2.5 mg/L (6 hr [Aerosol])
Ethylene oxide	Inhalation ATE	LC50 Rat: 700 ppmV (4 hr (Gas))
	Oral ATE	LD50 Rat: 100 mg/kg
1,4-dioxane	oral	LD50 Rat: 5150 mg/kg
	dermal	LD50 Rabbit: 7600 mg/kg
	inhalation	LC50 Rat: 9158 ppmV (4 hr - Vapor)
Formaldehyde	oral	LD50 Rat: 100 mg/kg
	inhalation	LC50 Rat: 3 mg/L (4 hr [vapor])
	dermal	LD50 Rat: 300 mg/kg
Dichloroacetic acid	dermal	LD50 Rabbit: 797 mg/kg
	oral	LD50 Rat: 2820 mg/kg
Pentasodium triphosphate	oral	LD50 Rat: >2000 mg/kg
	dermal	LD50 Rabbit: > 4640 mg/kg
	inhalation	LC50 Rat: 0.39 mg/L (4 hr [Aerosol])

# Skin Corrosion/Irritation

#### **Assessment:**

Causes severe skin burns and eye damage.

#### **Product Data:**

No data available.

# **Substance Data:**

Name	Result
Sodium hydroxide	Causes severe skin burns.
2-Butoxyethanol	Causes skin irritation.
2-dodecoxyethyl hydrogen sulfate	Causes skin irritation.
1-Propanaminium, 3-amino-N- (carboxymethyl)-N,N-dimethyl-, N-coco acyl derivs., hydroxides, inner salts	
Alcohols, C12-15, ethoxylated	Causes skin irritation.
Ethylene oxide	Causes severe skin burns.
Formaldehyde	Causes severe skin burns.
Dichloroacetic acid	Causes severe skin burns.

# Serious Eye Damage/Irritation

**Assessment:** 

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 05.14.2019

**Revision date:** 02.08.2024

**Clean Fast** 

Causes serious eye damage.

**Product Data:** No data available.

# **Substance Data:**

Name	Result
Sodium hydroxide	Causes serious eye damage.
D-Glucopyranose, oligomers, decyl octyl glycosides	Causes serious eye damage.
2-Butoxyethanol	Causes serious eye irritation.
2-dodecoxyethyl hydrogen sulfate	Causes serious eye irritation.
1-Propanaminium, 3-amino-N- (carboxymethyl)-N,N-dimethyl-, N-coco acyl derivs., hydroxides, inner salts	
Trisodium nitrilotriacetate	Causes serious eye irritation.
Alcohols, C12-15, ethoxylated	Causes serious eye damage.
Ethylene oxide	Causes serious eye damage.
1,4-dioxane	Causes serious eye irritation.
Formaldehyde	Causes serious eye damage.
Dichloroacetic acid	Causes serious eye damage.
Sodium Xylenesulfonate	Causes serious eye irritation.

# **Respiratory or Skin Sensitization**

**Assessment:** Based on available data, the classification criteria are not met.

Product Data: No data available. Substance Data:

Name	Result
Formaldehyde	May cause an allergic skin reaction.
1-Propanaminium, 3-amino-N- (carboxymethyl)-N,N-dimethyl-, N-coco acyl derivs., hydroxides, inner salts	

# Carcinogenicity

# **Assessment:**

Suspected of causing cancer. **Product Data:** No data available.

# **Substance Data:**

Name	Species	Result
Ethylene oxide		May cause cancer.
Formaldehyde		May cause cancer.
Trisodium nitrilotriacetate		Suspected of causing cancer.

Page 11 of 21

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 05.14.2019

**Revision date:** 02.08.2024

**Clean Fast** 

Name	Species	Result
1,4-dioxane		May cause cancer. 1,4-dioxane is characterized as "likely to be carcinogenic to humans." This characterization is based on the following findings: (1) inadequate evidence of carcinogenicity in humans, and (2) sufficient evidence in animals (i.e., hepatic tumors in multiple species [three strains of rats, two strains of mouse, and in guinea pigs] mesotheliomas of the peritoneum, mammary, and nasal tumors have also been observed in rats following 2 years of oral exposure to 1,4- dioxane). U.S. Environmental Protection Agency's Integrated Risk Information System (IRIS).
Dichloroacetic acid		Suspected of causing cancer.

# International Agency for Research on Cancer (IARC):

Name	Classification
Sodium hydroxide	Not Applicable
Sodium gluconate	Not Applicable
D-Glucopyranose, oligomers, decyl octyl glycosides	Not Applicable
2-dodecoxyethyl hydrogen sulfate	Not Applicable
Alcohols, C12-15, ethoxylated	Not Applicable
1-Propanaminium, 3-amino-N- (carboxymethyl)-N,N-dimethyl-, N-coco acyl derivs., hydroxides, inner salts	Not Applicable
Ethane-1,2-diol	Not Applicable
Ethylene oxide	Group 1
Formaldehyde	Group 1
Dichloroacetic acid	Group 2B
Pentasodium triphosphate	Not Applicable
2-Butoxyethanol	Group 3
Trisodium nitrilotriacetate	Group 2B
1,4-dioxane	Group 2B
Sodium Xylenesulfonate	Not Applicable

# **National Toxicology Program (NTP):**

Name	Classification
Sodium hydroxide	Not Applicable
Sodium gluconate	Not Applicable
D-Glucopyranose, oligomers, decyl octyl glycosides	Not Applicable
2-dodecoxyethyl hydrogen sulfate	Not Applicable
1-Propanaminium, 3-amino-N- (carboxymethyl)-N,N-dimethyl-, N-coco acyl derivs., hydroxides, inner salts	

Page 12 of 21

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

**Initial Preparation Date:** 05.14.2019

**Revision date:** 02.08.2024

#### **Clean Fast**

Name	Classification
Ethane-1,2-diol	Not Applicable
Ethylene oxide	Known to be human carcinogens
Formaldehyde	Known to be human carcinogens
Dichloroacetic acid	Reasonably anticipated to be human carcinogens
Pentasodium triphosphate	Not Applicable
2-Butoxyethanol	Not Applicable
Alcohols, C12-15, ethoxylated	Not Applicable
Trisodium nitrilotriacetate	Not Applicable
1,4-dioxane	Reasonably anticipated to be human carcinogens
Sodium Xylenesulfonate	Not Applicable

# **OSHA Carcinogens:**

Ingredient Name	CAS	OSHA Carcinogens Status
Formaldehyde	50-00-0	Yes

#### **Germ Cell Mutagenicity**

**Assessment:** Based on available data, the classification criteria are not met.

**Product Data:**No data available. **Substance Data:** 

Name	Result
Ethylene oxide	May cause genetic defects.
Formaldehyde	Suspected of causing genetic defects.

#### **Reproductive Toxicity**

**Assessment:** Based on available data, the classification criteria are not met.

**Product Data:**No data available. **Substance Data:** 

Name	Result	
Ethylene oxide	May damage fertility. Suspected of damaging the unborn child.	
Dichloroacetic acid	May damage fertility or the unborn child.	
	May cause harm to breast-fed children.	

# **Specific Target Organ Toxicity (Single Exposure)**

**Assessment:** Based on available data, the classification criteria are not met.

**Product Data:**No data available. **Substance Data:** 

Name	Result
Ethylene oxide	May cause respiratory irritation.
	May cause drowsiness or dizziness.
1,4-dioxane	May cause respiratory irritation.
Formaldehyde	May cause respiratory irritation.

Page 13 of 21

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 05.14.2019

**Revision date:** 02.08.2024

**Clean Fast** 

# **Specific Target Organ Toxicity (Repeated Exposure)**

#### **Assessment:**

May cause damage to organs through prolonged or repeated exposure.

#### **Product Data:**

No data available.

#### **Substance Data:**

Name	Result
Ethane-1,2-diol	May cause damage to Kidney through prolonged or repeated oral exposure.
Ethylene oxide	Studies on the effects of Ethylene oxide have concluded not only neurotoxic symptoms in humans, but also measured effects on nerve conduction velocities indicative of sensorimotor neuropathy, and axonal degeneration observed in nerve biopsies of exposed workers.
Dichloroacetic acid	May cause damage to organs (brain, liver, testes) through prolonged or repeated exposure

#### **Aspiration toxicity**

**Assessment:** Based on available data, the classification criteria are not met.

**Product Data:**No data available.

**Substance Data:** No data available.

# Information on Likely Routes of Exposure:

No data available.

# Symptoms Related to the Physical, Chemical, and Toxicological Characteristics:

No data available. **Other Information:**No data available.

# **SECTION 12: Ecological Information**

#### **Acute (Short-Term) Toxicity**

**Assessment:** Based on available data, the classification criteria are not met.

**Product Data:** No data available.

#### **Substance Data:**

Name	Result
2-Butoxyethanol	Aquatic Invertebrates EC50 Daphnia magna: 1550 mg/L (48 hr [mobility])
	Fish LC50 Oncorhynchus mykiss: 1474 mg/L (96 hr)
	Aquatic Plants EC50 Raphidocelis subcapitata: 623 mg/L (72 hr [biomass])
Sodium hydroxide	Aquatic Invertebrates EC50 Ceriodaphnia sp.: 40.4 mg/L (48 hr [immobilization])
	Fish LC50 Fish: 35 - 189 mg/L (96 hr)
D-Glucopyranose, oligomers, decyl octyl glycosides	Fish LC50 Danio rerio: 100.81 mg/L (96 hr)
	Aquatic Invertebrates EC50 Daphnia magna: > 100 mg/L (48 hr [mobility])
	Aquatic Plants EC50 Desmodesmus subspicatus: 27.22 mg/L (72 hr [growth rate])

Page 14 of 21

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 05.14.2019

**Revision date:** 02.08.2024

**Clean Fast** 

Name	Result
Alcohols, C12-15, ethoxylated	Aquatic Invertebrates EC50 Acartia tonsa: 0.88 mg/L (48 hr [mortality])
	Aquatic Plants EC50 Raphidocelis subcapitata: 0.031 mg/L (72 hr [growth rate])
	Fish LC50 Pimephales promelas: 0.628 mg/L (96 hr, QSAR)
1-Propanaminium, 3-amino-N-	Fish LC50 Danio rerio: 2 mg/L (96 hr)
(carboxymethyl)-N,N-dimethyl-, N-coco acyl derivs., hydroxides,	Aquatic Invertebrates EC50 Daphnia magna: 6.4 mg/L (48 hr [mobility])
inner salts	Aquatic Plants EC50 Ulva lactuca: 30 mg/L (48 hr [biomass])
Ethane-1,2-diol	Aquatic Plants EC50 Raphidocelis subcapitata: 6500 - 13,000 mg/L (96 hr [growth rate])
	Aquatic Invertebrates EC50 Daphnia magna: > 100 mg/L (48 hr)
	Fish LC50 Pimephales promelas: 72,860 mg/L (96 hr)
Ethylene oxide	Aquatic Plants EC50 Pseudokirchneriella subcapitata: 240 mg/L (96 h, read-across substance data)
	Aquatic Invertebrates LC50 Daphnia magna: 212 mg/L (48 h)
	Fish LC50 Pimephales promelas: 84 mg/L (96 h)
Dichloroacetic acid	Fish LC50 Marine water fish: >2000 mg/L (96 h)
	Aquatic Plants EC50 Marine water algae: 148.2 mg/L (72 h [cell number])
Pentasodium triphosphate	Fish LC50 Danio rerio: >1850 mg/L (24 hr)
	Aquatic Invertebrates EC50 Daphnia magna: >100 mg/L (48 hr [immobilisation])
Trisodium nitrilotriacetate	Fish LC50 Pimephales promelas: 114 mg/L (96 hr)
	Aquatic Plants EC50 Desmodesmus subspicatus: >100 mg/L (72 hr [growth rate])
	Aquatic Invertebrates EC50 Daphnia magna: 560 mg/L (96 hr [mortality])
Formaldehyde	Fish LC50 Morone saxatilis: 6.7 mg/L (96 hr)
	Aquatic Invertebrates EC50 Daphnia pulex: 5.8 mg/L (48 hr [mobility])
	Aquatic Plants EC50 Desmodesmus subspicatus: 3.48 mg/L (72 hr [biomass])
1,4-dioxane	Fish LC50 Pimephales promelas: 9850 mg/L (96 hr)
	Aquatic Invertebrates EC50 Daphnia magna: >1000 mg/L (48 hr)
	Aquatic Plants EC50 Pseudokirchneriella subcapitata: >1000 mg/L (72 hr)

# **Chronic (Long-Term) Toxicity**

**Assessment:** Based on available data, the classification criteria are not met.

**Product Data:** No data available.

#### **Substance Data:**

Januara Para.	
Name	Result
D-Glucopyranose, oligomers,	Fish NOEC Danio rerio: 1.8 mg/L (28 d [read-across])
decyl octyl glycosides	Aquatic Invertebrates NOEC Daphnia magna: 2 mg/L (21 d [read-across])
2-Butoxyethanol	Fish NOEC Danio rerio: > 100 mg/L (21 d [markers for endocrine disruptive effects])
	Aquatic Invertebrates NOEC Daphnia magna: 100 mg/L (21 d [reproduction])
Alcohols, C12-15, ethoxylated	Aquatic Invertebrates NOEC Daphnia magna: 0.036 mg/L (21 d [mortality])

Page 15 of 21

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 05.14.2019

**Revision date:** 02.08.2024

**Clean Fast** 

Name	Result
1-Propanaminium, 3-amino-N- (carboxymethyl)-N,N-dimethyl-, N-coco acyl derivs., hydroxides, inner salts	
Ethane-1,2-diol	Fish NOEC Menidia peninsulae: > 40 mg/L (28 d [mortality])
	Aquatic Invertebrates NOEC Daphnia magna: > 15,000 mg/L mg/L (21 d [reproduction])
Trisodium nitrilotriacetate	Aquatic Invertebrates LC50 Pagurus longicarpus: 1875 mg/L (7 d)
Formaldehyde	Aquatic Invertebrates NOEC Daphnia magna: 1.04 mg/L (21 d)
	Fish LC50 Danio rerio: 6.9 mg/L (6 d)
1,4-dioxane	Fish NOEC Pimephales promelas: 145 mg/L (32 d)
	Aquatic Invertebrates NOEC Daphnia magna: 1000 mg/L (21 d)

# **Persistence and Degradability**

**Product Data:** No data available.

#### **Substance Data:**

Name	Result
D-Glucopyranose, oligomers, decyl octyl glycosides	The substance is readily biodegradable in water. 100% degradation, measured by DOC removal, after 28 days.
Ethane-1,2-diol	The substance is Readily biodegradable. 90-100% degradation in water, measured by DOC removal, after 10 days.
Ethylene oxide	Readily biodegradable (96% degradation after 28 days, measured by TOC removal).
1,4-dioxane	Not readily biodegradable ( $< 10 \%$ degradation after 29 days, measured by CO2 evolution).
Formaldehyde	Substance is readily biodegradable 99% degradation measured by DOC removal after 28 days.
Dichloroacetic acid	The substance is readily biodegradable. 93% degradation, measured by Oxygen consumption, after 15 days.
Sodium hydroxide	Persistence assessment based on biodegradability is not relevant for inorganic compounds such as this substance.
Pentasodium triphosphate	Persistence assessment based on biodegradability is not relevant for inorganic compounds such as this substance.
2-Butoxyethanol	The substance is readily biodegradable. 90.4% degradation, measured by CO2 evolution, after 28 days.
Alcohols, C12-15, ethoxylated	The substance is readily biodegradable. $> 60 - \le 100\%$ degradation in water, after 28 days.
Trisodium nitrilotriacetate	Substance is readily biodegradable. >95% degradation in water, measured by DOC removal, after 28 days.
1-Propanaminium, 3-amino-N- (carboxymethyl)-N,N-dimethyl-, N-coco acyl derivs., hydroxides, inner salts	The substance is readily biodegradable. > 90% degradation (test mat. analysis), after 5 days.

# **Bioaccumulative Potential**

**Product Data:** No data available.

**Substance Data:** 

Page 16 of 21

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 05.14.2019

**Revision date:** 02.08.2024

# **Clean Fast**

Name	Result
1-Propanaminium, 3-amino-N- (carboxymethyl)-N,N-dimethyl-, N-coco acyl derivs., hydroxides, inner salts	The substance is not expected to bioaccumulate significantly (estimated BCF: 70.79 L/kg).
2-Butoxyethanol	The substance is not expected to bioaccumulate (log Kow = $0.83$ ).
Ethane-1,2-diol	The substance is not expected to bioaccumulate (log Pow=: -1.93).
Ethylene oxide	Low potential for bioaccumulation (logKow = $-0.3$ ).
Formaldehyde	Accumulation in aquatic organisms is not to be expected [BCF (aquatic species): 0.396 dimensionless].
Dichloroacetic acid	This substance has low potential for bioaccumulation.
Sodium hydroxide	Bioaccumulation assessment using a classic BCF assessment is not considered relevant for inorganic compounds such as this substance.
Pentasodium triphosphate	Bioaccumulation assessment using a classic BCF assessment is not considered relevant for inorganic compounds such as this substance.
Alcohols, C12-15, ethoxylated	The substance has the potential to bioaccumulate significantly (log Pow=5.79).
Trisodium nitrilotriacetate	Bioaccumulation is not expected. BCF (aquatic species): 3 L/kg ww
1,4-dioxane	Does not accumulate in aquatic organisms (mean BCF: 0.45).

# **Mobility in Soil**

**Product Data:** No data available.

# **Substance Data:**

Name	Result
(carboxymethyl)-N,N-dimethyl-,	The substance is mobile to moderately mobile (experimental log Koc: 1.812 dimensionless; calculated Koc: 648 L/kg); therefore, moderate adsorption to soil can be expected.
D-Glucopyranose, oligomers, decyl octyl glycosides	Substance is expected to be mobile (log Koc: 1.7); therefore, adsorption to soil is not expected.
Ethane-1,2-diol	Adsorption to the solid soil phase is not expected.
Formaldehyde	Adsorption to solid soil phase is possible. [Koc at 20 °C: 15.9]
Dichloroacetic acid	This substance will not adsorb at all to soils or sediments should these environmental compartments be exposed to it.
Sodium hydroxide	Mobility in soil assessment based on KOC/Kd values are not relevant for inorganic compounds such as this substance.
Pentasodium triphosphate	The substance is moderately mobile, therefore, slight adsorption to soil is expected (log Koc=2.15)
Alcohols, C12-15, ethoxylated	The substance is moderately to hardly mobile therefore, adsorption to soil is expected ((log Koc=2.301 to 3.352 (MCI method) and log Koc=3.7 to 4.8 (Van Compernolle et al. (2006) method.))
Trisodium nitrilotriacetate	The substance has a low potential for adsorption to soil and sediment. log Kp (sediment-water): 1.6 L/kg
1,4-dioxane	Significant adsorption to solid soil phase is not expected (calculated log Koc: 0.51 at 25 °C).

# Results of PBT and vPvB assessment

# **Product Data:**

**PBT assessment:** This product does not contain any substances that are assessed to be a PBT.

Page 17 of 21

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 05.14.2019 Page

**Revision date: 02.08.2024** 

**Clean Fast** 

**vPvB** assessment: This product does not contain any substances that are assessed to be a vPvB.

#### **Substance Data:**

# PBT assessment:

D-Glucopyranose, oligomers, decyl octyl glycosides	The substance is not PBT.
Alcohols, C12-15, ethoxylated	The substance is not PBT.
1-Propanaminium, 3-amino-N- (carboxymethyl)-N,N- dimethyl-, N-coco acyl derivs., hydroxides, inner salts	The substance is not PBT.
Trisodium nitrilotriacetate	The substance is not PBT.
2-Butoxyethanol	The substance is not PBT.
Ethane-1,2-diol	The substance is not PBT.
Ethylene oxide	This substance is not PBT.
Formaldehyde	Not a PBT substance.
Dichloroacetic acid	The substance is not PBT.
Sodium hydroxide	PBT assessment does not apply to inorganic compounds such as this substance.
Pentasodium triphosphate	PBT assessment does not apply to inorganic compounds such as this substance.
1,4-dioxane	Under assessment as Persistent, Bioaccumulative and Toxic (PBT list).

#### vPvB assessment:

VI VD G55C55IIICIICI	
D-Glucopyranose, oligomers, decyl octyl glycosides	The substance is not vPvB.
Alcohols, C12-15, ethoxylated	The substance is not vPvB.
1-Propanaminium, 3-amino-N- (carboxymethyl)-N,N- dimethyl-, N-coco acyl derivs., hydroxides, inner salts	The substance is not vPvB.
Trisodium nitrilotriacetate	The substance is not vPvB.
2-Butoxyethanol	The substance is not vPvB.
Ethane-1,2-diol	The substance is not vPvB.
Ethylene oxide	This substance is not vPvB.
Formaldehyde	Not a vPvB substance.
Dichloroacetic acid	The substance is not vPvB.
Sodium hydroxide	vPvB assessment does not apply to inorganic compounds such as this substance.
Pentasodium triphosphate	vPvB assessment does not apply to inorganic compounds such as this substance.
1,4-dioxane	This substance is not vPvB.

Other Adverse Effects: No data available.

# **SECTION 13: Disposal Considerations**

# **Disposal Methods:**

It is the responsibility of the waste generator to characterize all waste materials according to applicable regulatory entities.

Page 18 of 21

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

**Initial Preparation Date:** 05.14.2019

**Revision date: 02.08.2024** 

**Clean Fast** 

#### Contaminated packages:

Not determined or not applicable.

# **SECTION 14: Transport Information**

#### United States Transportation of Dangerous Goods (49 CFR DOT)

UN Number	1824
UN Proper Shipping Name	Sodium Hydroxide, Solution
UN Transport Hazard Class(es)	8
Packing Group	II
<b>Environmental Hazards</b>	None
Special Precautions for User	None

#### **International Maritime Dangerous Goods (IMDG)**

UN Number	Not regulated
UN Proper Shipping Name	Not regulated
UN Transport Hazard Class(es)	None
Packing Group	None
Environmental Hazards	None
Special Precautions for User	None

# International Air Transport Association Dangerous Goods Regulations (IATA-DGR)

UN Number	Not regulated
UN Proper Shipping Name	Not regulated
UN Transport Hazard Class(es)	None
Packing Group	None
Environmental Hazards	None
Special Precautions for User	None

# **SECTION 15: Regulatory Information**

#### **United States Regulations**

**Inventory Listing (TSCA):** All ingredients are listed-active or exempt.

**Significant New Use Rule (TSCA Section 5):** None of the ingredients are listed. **Export Notification under TSCA Section 12(b):** None of the ingredients are listed.

# **SARA Section 302 Extremely Hazardous Substances:**

75-21-8	Ethylene oxide	Listed
50-00-0	Formaldehyde	Listed

# **SARA Section 313 Toxic Chemicals:**

111-76-2	2-Butoxyethanol	Listed
107-21-1	Ethane-1,2-diol	Listed
75-21-8	Ethylene oxide	Listed

Page 19 of 21

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 05.14.2019 Page 20 of 21

Revision date: 02.08.2024

	ear	, E	20+
u	eai	ΙГ	ası

50-00-0	Formaldehyde		Listed
5064-31-3	Trisodium nitrilotriacetate		Listed
123-91-1	1,4-dioxane		Listed
CERCLA:	•		
1310-73-2	Sodium hydroxide	Listed	1000 lb
111-76-2	2-Butoxyethanol	Listed	N/A
107-21-1	Ethane-1,2-diol	Listed	5000 lbs
75-21-8	Ethylene oxide Listed		10 lbs
50-00-0	Formaldehyde	Listed	100 lb
123-91-1	1,4-dioxane	Listed	100 lbs
RCRA:	•		•
75-21-8	Ethylene oxide	Listed	U115
50-00-0	Formaldehyde	Listed	U122
123-91-1	1,4-dioxane	Listed	U108
Section 112(r) of	the Clean Air Act (CAA):	•	•
107-21-1	Ethane-1,2-diol		Listed
75-21-8	Ethylene oxide		Listed
50-00-0	Formaldehyde		Listed
Massachusetts Ri	ght to Know:		•
1310-73-2	Sodium hydroxide		Listed
107-21-1	Ethane-1,2-diol		Listed
75-21-8	Ethylene oxide		Listed
7758-29-4	Pentasodium triphosphate		Listed
111-76-2			Listed
5064-31-3	Trisodium nitrilotriacetate		Listed
50-00-0	Formaldehyde Liste		Listed
123-91-1	1,4-dioxane Listed		Listed
New Jersey Right	to Know:		
1310-73-2	Sodium hydroxide		Listed
107-21-1	Ethane-1,2-diol		Listed
75-21-8	Ethylene oxide		Listed
79-43-6	Dichloroacetic acid		Listed
111-76-2	2-Butoxyethanol		Listed
50-00-0	Formaldehyde		Listed
123-91-1	1,4-dioxane		Listed
New York Right to			
1310-73-2	Sodium hydroxide		Listed
107-21-1	Ethane-1,2-diol		Listed
75-21-8	Ethylene oxide		Listed
79-43-6	Dichloroacetic acid		Listed
7758-29-4	-29-4 Pentasodium triphosphate		Listed
111-76-2	2-Butoxyethanol		Listed

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 05.14.2019 Page 2

**Revision date: 02.08.2024** 

#### **Clean Fast**

50-00-0	Formaldehyde	Listed
123-91-1	1,4-dioxane	Listed

#### Pennsylvania Right to Know:

1310-73-2	Sodium hydroxide	Listed
107-21-1	Ethane-1,2-diol	Listed
75-21-8	Ethylene oxide	Listed
7758-29-4	Pentasodium triphosphate	Listed
111-76-2	2-Butoxyethanol	Listed
50-00-0	Formaldehyde	Listed
123-91-1	1,4-dioxane	Listed

#### **California Proposition 65:**

▲WARNING: This product can expose you to chemicals including Formaldehyde and 1,4-dioxane; which are known to the State of California to cause cancer; and Ethane-1,2-diol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

▲WARNING: This product can expose you to chemicals including Ethylene oxide and Dichloroacetic acid; which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Additional information: Not determined.

#### **SECTION 16: Other Information**

### **Abbreviations and Acronyms:** None

# **Disclaimer:**

This product has been classified in accordance with OSHA HCS 2012 guidelines. The information provided in this SDS is correct, to the best of our knowledge, based on information available. The information given is designed only as a guidance for safe handling, use, storage, transportation and disposal and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials, unless specified in the text. The responsibility to provide a safe workplace remains with the user.

**NFPA:** 0-0-0 **HMIS:** 0-0-0

**Initial Preparation Date:** 05.14.2019

**Revision date:** 02.08.2024

**End of Safety Data Sheet** 

Page 21 of 21