

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 02.18.2025

Page 1 of 13

Revision date: 02.18.2025

High Shine Paint Protectant

SECTION 1: Identification

Product Identifier

Product Name: High Shine Paint Protectant

Product code: C-8604

Recommended Use of the Product and Restriction on Use

Relevant Identified Uses: Drying Agent

Uses Advised Against: NA

Reasons Why Uses Advised Against: Not determined or not applicable.

Manufacturer or Supplier Details

Manufacturer:

United States

Heiden Industries

1200 Veterans Blvd.

Kenner, LA. 70062

8008784913

TODD@HEIDENIND.COM

Emergency Telephone Number:

North America

CHEMTREC

800-424-9300 (24 hours)

SECTION 2: Hazard(s) Identification

GHS Classification:

Skin corrosion, category 1B

Eye irritation, category 2A

Specific target organ toxicity - single exposure, category 3, narcotic effects

Label elements

Hazard Pictograms:



Signal Word: Danger

Hazard statements:

H336 May cause drowsiness or dizziness

H314 Causes severe skin burns and eye damage

H319 Causes serious eye irritation

Precautionary Statements:

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P271 Use only outdoors or in a well-ventilated area

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 02.18.2025

Page 2 of 13

Revision date: 02.18.2025

High Shine Paint Protectant

P264 Wash hands thoroughly after handling

P280 Wear protective gloves/protective clothing/eye protection/face protection

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

P363 Wash contaminated clothing before reuse

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P337+P313 If eye irritation persists: Get medical advice/attention

P403+P233 Store in a well-ventilated place. Keep container tightly closed

P405 Store locked up

P501 It is the responsibility of the waste generator to characterize all waste material according to regulatory entities.

Hazards Not Otherwise Classified: None

SECTION 3: Composition/Information on Ingredients

Identification	Name	Weight %
CAS Number: 64741-44-2	Distillates (petroleum), straight-run middle	<55
CAS Number: Proprietary	Proprietary Quaternary Ammonium Salt	<32
CAS Number: 111-76-2	Ethylene Glycol Monobutyl Ether	<25
CAS Number: 68155-39-5	Amines, C14-18 and C16-18-unsaturated alkyl, ethoxylated	<20
CAS Number: 68439-46-3	Alcohols, C9-11, branched and linear, ethoxylated	<8
CAS Number: 107-41-5	Hexylene glycol	<4
CAS Number: 107-21-1	Ethane-1,2-diol	<0.018

Additional Information: None

SECTION 4: First Aid Measures

Description of First Aid Measures

General Notes:

Show this Safety Data Sheet to the doctor in attendance.

After Inhalation:

If inhaled, remove person to fresh air. Keep person at rest. If symptoms persists, seek medical advice.

After Skin Contact:

Remove contaminated clothing and shoes. Rinse skin with copious amounts of water [shower] for several minutes. Launder contaminated clothing before reuse. If symptoms develop or persist, seek medical advice/attention.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 02.18.2025

Page 3 of 13

Revision date: 02.18.2025

High Shine Paint Protectant

After Eye Contact:

Immediately rinse eyes with plenty of gently flowing lukewarm water for 15 minutes. Remove contact lenses if present and easy to do so. Protect unexposed eye. Seek immediate medical attention, preferably from an ophthalmologist.

After Swallowing:

If swallowed, DO NOT induce vomiting unless told to do so by a physician or poison control center. Rinse mouth with water. Never give anything by mouth to an unconscious person. If spontaneous vomiting occurs, place on the left side with head down to prevent aspiration of liquid into the lungs. If symptoms develop or persist, seek medical advice/attention.

Most Important Symptoms and Effects, Both Acute and Delayed

Acute Symptoms and Effects:

Exposure to skin may result in redness, pain, burning, inflammation and tissue damage. Exposure to eyes may result in irritation, redness, pain, inflammation, itching, burning, tearing, corneal damage and loss of vision. Exposure via inhalation may result in cough, sore throat, burning sensation and shortness of breath. Exposure via ingestion may result in burns of the mouth and throat, abdominal pain, burning sensation in the throat and chest, nausea, vomiting, shock or collapse.

Delayed Symptoms and Effects:

Effects are dependent on exposure (dose, concentration, contact time).

Immediate Medical Attention and Special Treatment

Specific Treatment:

Overexposure via inhalation requires urgent medical treatment.

In case of eye contact, seek prompt medical attention while rinsing is continued.

In case of skin contact, seek prompt medical attention while rinsing is continued.

In case of ingestion, seek prompt medical attention.

Notes for the Doctor:

Treat symptomatically.

SECTION 5: Firefighting Measures

Extinguishing Media

Suitable Extinguishing Media:

Water mist/fog, carbon dioxide, dry chemical or alcohol resistant foam.

Unsuitable Extinguishing Media:

Do not use water jet.

Specific Hazards During Fire-Fighting:

Thermal decomposition may produce irritating/toxic fumes/gases.

Special Protective Equipment for Firefighters:

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full-face piece operated in positive pressure mode.

Special precautions:

Avoid contact with skin, eyes, hair and clothing. Do not breathe fumes/gas/mists/aerosols/vapors/dusts.

Move containers from fire area if safe to do so. Use water spray/fog for cooling fire exposed containers.

Avoid unnecessary run-off of extinguishing media which may cause pollution.

SECTION 6: Accidental Release Measures

Personal Precautions, Protective Equipment, and Emergency Procedures:

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 02.18.2025

Page 4 of 13

Revision date: 02.18.2025

High Shine Paint Protectant

Evacuate unnecessary personnel. Ventilate area. Extinguish any sources of ignition. Wear recommended personal protective equipment (see Section 8). Avoid contact with skin, eyes and clothing. Avoid breathing mist, vapor, dust, fume and spray. Do not walk through spilled material. Wash thoroughly after handling.

Environmental Precautions:

Prevent further leakage or spillage if safe to do so. Prevent from reaching drains, sewers and waterways. Discharge into the environment must be avoided.

Methods and Material for Containment and Cleaning Up:

Do not touch damaged containers or spilled material unless wearing appropriate personal protective clothing. Stop leak if you can do it without risk. Contain and collect spillage and place in suitable container for future disposal. Dispose of in accordance with all applicable regulations (see Section 13).

Reference to Other Sections:

For personal protective equipment see Section 8. For disposal see Section 13.

SECTION 7: Handling and Storage

Precautions for Safe Handling:

Use appropriate personal protective equipment (see Section 8). Use only with adequate ventilation. Avoid breathing mist/vapor/spray/dust. Do not eat, drink, smoke, or use personal products when handling chemical substances. Avoid contact with skin, eyes and clothing. Wash affected areas thoroughly after handling. Keep away from incompatible materials (See Section 10). Keep containers tightly closed when not in use.

Conditions for Safe Storage, Including Any Incompatibilities:

Store in cool, dry, well-ventilated location out of direct sunlight. Keep away from food and beverages. Protect from freezing and physical damage. Store away from heat, open flames and other sources of ignition. Keep container tightly sealed. Store away from incompatible materials (See Section 10).

SECTION 8: Exposure Controls/Personal Protection

Only those substances with limit values have been included below.

Occupational Exposure Limit Values:

Country (Legal Basis)	Substance	Identifier	Permissible concentration
OSHA	Ethylene Glycol Monobutyl Ether	111-76-2	8-Hour TWA-PEL: 240 mg/m ³ (50 ppm)
	Ethane-1,2-diol	107-21-1	Ceiling Limit: 125 mg/m ³
	Ethane-1,2-diol	107-21-1	Ceiling Limit: 50 ppm
NIOSH	Ethylene Glycol Monobutyl Ether	111-76-2	IDLH: 700 ppm
	Ethylene Glycol Monobutyl Ether	111-76-2	REL-TWA: 24 mg/m ³ (5 ppm [up to 10 hr])
	Ethane-1,2-diol	107-21-1	Ceiling Limit: 50 ppm
ACGIH	Ethylene Glycol Monobutyl Ether	111-76-2	8-Hour TWA: 20 ppm
	Ethane-1,2-diol	107-21-1	8-Hour TWA: 25 ppm (vapor fraction)
	Ethane-1,2-diol	107-21-1	15-Minute STEL: 50 ppm (vapor fraction)
	Ethane-1,2-diol	107-21-1	15-Minute STEL: 10 mg/m ³ (aerosol only, inhalable fraction)
United States(California)	Ethylene Glycol Monobutyl Ether	111-76-2	8-Hour TWA-PEL: 97 mg/m ³ (20 ppm)

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 02.18.2025

Page 5 of 13

Revision date: 02.18.2025

High Shine Paint Protectant

Country (Legal Basis)	Substance	Identifier	Permissible concentration
	Ethane-1,2-diol	107-21-1	Ceiling Limit: 100 mg/m ³ (40 ppm)

Biological Limit Values:

Country (Legal Basis)	Substance	Identifier	Determinant	Specimen	Sampling time	Permissible limits
ACGIH	Ethylene Glycol Monobutyl Ether	111-76-2	Butoxyacetic acid (with hydrolysis)	Creatinine in Urine	End of shift	200 mg/g

Information on Monitoring Procedures:

Not determined or not applicable.

Appropriate Engineering Controls:

Emergency eye wash stations and safety showers should be available in the immediate vicinity of use or handling. Provide adequate ventilation to maintain the airborne concentrations of vapor, mists, and/or dusts below the applicable workplace exposure limits, while observing recognized national standards (or equivalent).

Personal Protection Equipment

Eye and Face Protection:

Safety glasses or goggles. Use eye protection equipment that has been tested and approved by recognized national standards (or equivalent).

Skin and Body Protection:

Not determined or not applicable.

Respiratory Protection:

If engineering controls do not maintain airborne concentrations below the applicable workplace exposure limits, or to an acceptable level (if exposure limits have not been established), a respirator approved by recognized national standards (or equivalent) must be worn.

General Hygienic Measures:

When handling chemical products, do not eat, drink or smoke. Wash hands after handling, before breaks, and at the end of the workday. Avoid contact with skin, eyes and clothing. Wash contaminated clothing before reuse. Perform routine housekeeping.

SECTION 9: Physical and Chemical Properties

Information on Basic Physical and Chemical Properties

Appearance	Liquid
Odor	Std.
Odor threshold	Not determined or not available.
pH	7
Melting point/freezing point	Not determined or not available.
Initial boiling point/range	Not determined or not available.
Flash point (closed cup)	Not determined or not available.
Evaporation rate	Not determined or not available.
Flammability (solid, gas)	Not determined or not available.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 02.18.2025

Page 6 of 13

Revision date: 02.18.2025

High Shine Paint Protectant

Upper flammability/explosive limit	Not determined or not available.
Lower flammability/explosive limit	Not determined or not available.
Vapor pressure	Not determined or not available.
Vapor density	Not determined or not available.
Density	Not determined or not available.
Relative density	Not determined or not available.
Solubilities	Not determined or not available.
Partition coefficient (n-octanol/water)	Not determined or not available.
Auto/Self-ignition temperature	Not determined or not available.
Decomposition temperature	Not determined or not available.
Dynamic viscosity	Not determined or not available.
Kinematic viscosity	Not determined or not available.
Explosive properties	Not determined or not available.
Oxidizing properties	Not determined or not available.

SECTION 10: Stability and Reactivity

Reactivity:

Not reactive under recommended handling and storage conditions.

Chemical Stability:

Stable under recommended handling and storage conditions.

Possibility of Hazardous Reactions:

Hazardous reactions are not anticipated under recommended conditions of handling and storage.

Conditions to Avoid:

Avoid generation of aerosols and mists, extreme heat, open flames, hot surfaces, sparks, ignition sources and incompatible materials.

Extreme heat, open flames, hot surfaces, sparks, ignition sources and incompatible materials.

Incompatible Materials:

None known.

Hazardous Decomposition Products:

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological Information

Acute Toxicity

Assessment: Based on available data, the classification criteria are not met.

Product Data: No data available.

Substance Data:

Name	Route	Result
Distillates (petroleum), straight-run middle	inhalation	LC50 Rat: >2.53 mg/L (4 hr [aerosol])
	oral	LD50 Rat: > 5000 mg/kg
	dermal	LD50 Rabbit: > 2000 mg/kg
Ethylene Glycol Monobutyl Ether	Dermal ATE	LD50 Rabbit: 1100 mg/kg
	Oral ATE	LD50 Rat: 1200 mg/kg (Annex VI to the CLP)
	Inhalation ATE	LC50 Rat: 3 mg/L (4 hr [Vapor] Annex VI to the CLP)

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 02.18.2025

Page 7 of 13

Revision date: 02.18.2025

High Shine Paint Protectant

Name	Route	Result
Amines, C14-18 and C16-18-unsaturated alkyl, ethoxylated	Oral ATE	LD50 Rat: 500 mg/kg
Ethane-1,2-diol	Oral ATE	LD50 Rat: 500 mg/kg
Alcohols, C9-11, branched and linear, ethoxylated	oral	LD50 Rat: 1400 mg/kg
	dermal	LD50 Rabbit: > 2000 mg/kg ([Read-across substance data])
	inhalation	LC50 Rat: >1.6 mg/L (4 hr [aerosol, Read-across substance data])

Skin Corrosion/Irritation

Assessment:

Causes severe skin burns and eye damage.

Product Data:

No data available.

Substance Data:

Name	Result
Amines, C14-18 and C16-18-unsaturated alkyl, ethoxylated	Causes skin irritation.
Ethylene Glycol Monobutyl Ether	Causes skin irritation.

Serious Eye Damage/Irritation

Assessment:

Causes serious eye irritation.

Product Data:

No data available.

Substance Data:

Name	Result
Amines, C14-18 and C16-18-unsaturated alkyl, ethoxylated	Causes serious eye damage.
Ethylene Glycol Monobutyl Ether	Causes serious eye irritation.
Alcohols, C9-11, branched and linear, ethoxylated	Causes serious eye damage.

Respiratory or Skin Sensitization

Assessment: Based on available data, the classification criteria are not met.

Product Data:

No data available.

Substance Data: No data available.

Carcinogenicity

Assessment: Based on available data, the classification criteria are not met.

Product Data: No data available.

Substance Data: No data available.

International Agency for Research on Cancer (IARC):

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 02.18.2025

Page 8 of 13

Revision date: 02.18.2025

High Shine Paint Protectant

Name	Classification
Distillates (petroleum), straight-run middle	Not Applicable
Amines, C14-18 and C16-18-unsaturated alkyl, ethoxylated	Not Applicable
Ethylene Glycol Monobutyl Ether	Group 3
Ethane-1,2-diol	Not Applicable
Alcohols, C9-11, branched and linear, ethoxylated	Not Applicable

National Toxicology Program (NTP):

Name	Classification
Distillates (petroleum), straight-run middle	Not Applicable
Amines, C14-18 and C16-18-unsaturated alkyl, ethoxylated	Not Applicable
Ethylene Glycol Monobutyl Ether	Not Applicable
Ethane-1,2-diol	Not Applicable
Alcohols, C9-11, branched and linear, ethoxylated	Not Applicable

OSHA Carcinogens: Not applicable

Germ Cell Mutagenicity

Assessment: Based on available data, the classification criteria are not met.

Product Data:

No data available.

Substance Data: No data available.

Reproductive Toxicity

Assessment: Based on available data, the classification criteria are not met.

Product Data:

No data available.

Substance Data: No data available.

Specific Target Organ Toxicity (Single Exposure)

Assessment:

May cause drowsiness or dizziness.

Product Data:

No data available.

Substance Data: No data available.

Specific Target Organ Toxicity (Repeated Exposure)

Assessment: Based on available data, the classification criteria are not met.

Product Data:

No data available.

Substance Data:

Name	Result
------	--------

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 02.18.2025

Page 9 of 13

Revision date: 02.18.2025

High Shine Paint Protectant

Name	Result
Distillates (petroleum), straight-run middle	May cause damage to spleen, liver, and bone marrow through prolonged or repeated exposure.
Ethane-1,2-diol	May cause damage to Kidney through prolonged or repeated oral exposure.

Aspiration toxicity

Assessment: Based on available data, the classification criteria are not met.

Product Data:

No data available.

Substance Data:

Name	Result
Distillates (petroleum), straight-run middle	May be fatal if swallowed and enters airways.

Information on Likely Routes of Exposure:

No data available.

Symptoms Related to the Physical, Chemical, and Toxicological Characteristics:

No data available.

Other Information:

No data available.

SECTION 12: Ecological Information

Acute (Short-Term) Toxicity

Assessment: Based on available data, the classification criteria are not met.

Product Data: No data available.

Substance Data:

Name	Result
Ethylene Glycol Monobutyl Ether	Aquatic Invertebrates EC50 Daphnia magna: 1550 mg/L (48 hr [mobility])
	Fish LC50 Oncorhynchus mykiss: 1474 mg/L (96 hr [mortality])
	Aquatic Plants EC50 Raphidocelis subcapitata: 1840 mg/L (72 hr [Growth rate])
Ethane-1,2-diol	Aquatic Invertebrates EC50 Daphnia magna: > 100 mg/L (48 hr [immobilisation])
	Fish LC50 Pimephales promelas: 53000 mg/L (96 hr [mortality])
Distillates (petroleum), straight-run middle	Aquatic Invertebrates EC50 Daphnia magna: 2 mg/L (48 hr [mobility; read across])
	Aquatic Plants EC50 Raphidocelis subcapitata: 22 mg/L (72 hr [growth rate; read across])
Alcohols, C9-11, branched and linear, ethoxylated	Fish LC50 Oncorhynchus mykiss: 5 - 7 mg/L (96 hr)
	Aquatic Invertebrates EC50 Daphnia magna: 2.5 mg/L (48 hr [mobility])
	Aquatic Plants EC50 Raphidocelis subcapitata: 1.4 mg/L (96 hr [cell number])

Chronic (Long-Term) Toxicity

Assessment: Based on available data, the classification criteria are not met.

Product Data: No data available.

Substance Data:

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 02.18.2025

Page 10 of 13

Revision date: 02.18.2025

High Shine Paint Protectant

Name	Result
Ethylene Glycol Monobutyl Ether	Fish NOEC Danio rerio: > 100 mg/L (21 d [markers for endocrine disruptive effects])
	Aquatic Invertebrates NOEC Daphnia magna: 100 mg/L (21 d [reproduction])
	Aquatic Plants NOEC Raphidocelis subcapitata: 286 mg/L (72 hr [Growth rate])
Ethane-1,2-diol	Fish NOEC Menidia peninsulae: > 40 mg/L (28 d [weight and mortality, Read-across substance data])
	Aquatic Invertebrates NOEC Daphnia magna: 7500 - 15000 mg/L (21 d [growth, Read-across substance data])
	Aquatic Plants NOEC Raphidocelis subcapitata: > 100 mg/L (72 hr [growth rate])
Alcohols, C9-11, branched and linear, ethoxylated	Fish NOEC Pimephales promelas: 0.28 mg/L (30 d [mortality, Read-across substance data])
	Aquatic Invertebrates NOEC Daphnia magna: 0.77 mg/L (21 d [reproduction, Read-across substance data])

Persistence and Degradability

Product Data: No data available.

Substance Data:

Name	Result
Distillates (petroleum), straight-run middle	Standard biodegradation studies are not applicable to petroleum UVCB substances.
Ethane-1,2-diol	The substance is readily biodegradable. 90-100% degradation in water, measured by DOC removal, after 10 days.
Ethylene Glycol Monobutyl Ether	The substance is readily biodegradable. 90.4% degradation, measured by CO ₂ evolution, after 28 days.
Alcohols, C9-11, branched and linear, ethoxylated	The substance is readily biodegradable. 72% degradation in water, measured by inorganic C analysis, after 28 days (Read-across substance data).

Bioaccumulative Potential

Product Data: No data available.

Substance Data:

Name	Result
Ethane-1,2-diol	The substance is not expected to bioaccumulate (log Pow: -1.36).
Distillates (petroleum), straight-run middle	Standard bioaccumulation studies are not applicable to petroleum UVCB substances.
Ethylene Glycol Monobutyl Ether	The substance is not expected to bioaccumulate (log Kow = 0.83).
Alcohols, C9-11, branched and linear, ethoxylated	The substance has the potential to bioaccumulate (log Pow=3.3 - 3.73 & BCF= 237 L/kg, Read-across substance data).

Mobility in Soil

Product Data: No data available.

Substance Data:

Name	Result
Distillates (petroleum), straight-run middle	Standard adsorption/desorption studies are not applicable to petroleum UVCB substances.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 02.18.2025

Page 11 of 13

Revision date: 02.18.2025

High Shine Paint Protectant

Name	Result
Ethane-1,2-diol	The end point is not applicable because the the substance has a low octanol water partition coefficient and its relevant degradation products decompose rapidly.
Alcohols, C9-11, branched and linear, ethoxylated	The substance is slightly mobile, therefore, adsorption to soil and sediment is expected (log Koc=2.7 - 3.5 at 25 °C, QSAR substance data).

Results of PBT and vPvB assessment

Product Data:

PBT assessment: This product does not contain any substances that are assessed to be a PBT.

vPvB assessment: This product does not contain any substances that are assessed to be a vPvB.

Substance Data:

PBT assessment:

Distillates (petroleum), straight-run middle	The substance is not PBT.
Ethylene Glycol Monobutyl Ether	The substance is not PBT.
Ethane-1,2-diol	The substance is not PBT.
Alcohols, C9-11, branched and linear, ethoxylated	The substance is not PBT.

vPvB assessment:

Distillates (petroleum), straight-run middle	The substance is not vPvB.
Ethylene Glycol Monobutyl Ether	The substance is not vPvB.
Ethane-1,2-diol	The substance is not vPvB.
Alcohols, C9-11, branched and linear, ethoxylated	The substance is not vPvB.

Other Adverse Effects: No data available.

SECTION 13: Disposal Considerations

Disposal Methods:

It is the responsibility of the waste generator to characterize all waste material according to regulatory entities.

Contaminated packages:

Not determined or not applicable.

SECTION 14: Transport Information

United States Transportation of Dangerous Goods (49 CFR DOT)

UN Number	Not Regulated
UN Proper Shipping Name	Not regulated
UN Transport Hazard Class(es)	None
Packing Group	None
Environmental Hazards	None
Special Precautions for User	None

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 02.18.2025

Page 12 of 13

Revision date: 02.18.2025

High Shine Paint Protectant

International Maritime Dangerous Goods (IMDG)

UN Number	Not regulated
UN Proper Shipping Name	Not regulated
UN Transport Hazard Class(es)	None
Packing Group	None
Environmental Hazards	None
Special Precautions for User	None

International Air Transport Association Dangerous Goods Regulations (IATA-DGR)

UN Number	Not regulated
UN Proper Shipping Name	Not regulated
UN Transport Hazard Class(es)	None
Packing Group	None
Environmental Hazards	None
Special Precautions for User	None

SECTION 15: Regulatory Information

United States Regulations

Inventory Listing (TSCA): All ingredients are listed-active or exempt.

Significant New Use Rule (TSCA Section 5): None of the ingredients are listed.

Export Notification under TSCA Section 12(b): None of the ingredients are listed.

SARA Section 302 Extremely Hazardous Substances: None of the ingredients are listed.

SARA Section 313 Toxic Chemicals:

111-76-2	Ethylene Glycol Monobutyl Ether	Listed
107-21-1	Ethane-1,2-diol	Listed

CERCLA:

111-76-2	Ethylene Glycol Monobutyl Ether	Listed	N/A
107-21-1	Ethane-1,2-diol	Listed	5000 lbs
64741-44-2	Distillates (petroleum), straight-run middle	Listed	100 lbs for D001

RCRA:

64741-44-2	Distillates (petroleum), straight-run middle	Listed	D001
------------	----------------------------------------------	--------	------

Section 112(r) of the Clean Air Act (CAA): None of the ingredients are listed.

Massachusetts Right to Know:

107-21-1	Ethane-1,2-diol	Listed
111-76-2	Ethylene Glycol Monobutyl Ether	Listed
107-41-5	Hexylene glycol	Listed

New Jersey Right to Know:

107-21-1	Ethane-1,2-diol	Listed
111-76-2	Ethylene Glycol Monobutyl Ether	Listed

New York Right to Know:

107-21-1	Ethane-1,2-diol	Listed
----------	-----------------	--------

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 02.18.2025

Page 13 of 13

Revision date: 02.18.2025

High Shine Paint Protectant

64741-44-2	Distillates (petroleum), straight-run middle	Listed
111-76-2	Ethylene Glycol Monobutyl Ether	Listed

Pennsylvania Right to Know:

107-21-1	Ethane-1,2-diol	Listed
111-76-2	Ethylene Glycol Monobutyl Ether	Listed
107-41-5	Hexylene glycol	Listed

California Proposition 65: None of the ingredients are listed.

Additional information: Not determined.

SECTION 16: Other Information

Abbreviations and Acronyms: None

Disclaimer:

This product has been classified in accordance with OSHA HCS 2012 guidelines. The information provided in this SDS is correct, to the best of our knowledge, based on information available. The information given is designed only as a guidance for safe handling, use, storage, transportation and disposal and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials, unless specified in the text. The responsibility to provide a safe workplace remains with the user.

NFPA: 0-0-0

HMIS: 0-0-0

Initial Preparation Date: 02.18.2025

Revision date: 02.18.2025

End of Safety Data Sheet