

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 02.08.2024 Page 1 of 16

Revision date: 02.08.2024

Power Maxx Orange

SECTION 1: Identification

Product Identifier

Product Name: Power Maxx Orange

Product code: C-8702

Recommended Use of the Product and Restriction on Use

Relevant Identified Uses: For use in Car Wash Equipment

Uses Advised Against: Intentional direct skin contact, due to irritation

and chronic effects with long term exposure.

Reasons Why Uses Advised Against: Irritancy and possible chronic

effects with heavy, regular exposure.

Manufacturer or Supplier Details

Manufacturer:

United States

Heiden Industries 1200 Veterans Blvd. Kenner, LA. 70062 8008784913 TODD@HEIDENIND.COM

Emergency Telephone Number:

North America

CHEMTREC 800-424-9300 (24 hours)

SECTION 2: Hazard(s) Identification

GHS Classification:

Skin corrosion, category 1A
Serious eye damage, category 1
Skin sensitization, category 1
Carcinogenicity, category 2

Specific target organ toxicity - single exposure, category 3, narcotic effects

Label elements

Hazard Pictograms:







Signal Word: Danger **Hazard statements:**

H314 Causes severe skin burns and eye damage

H318 Causes serious eye damage

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 02.08.2024

Revision date: 02.08.2024

Power Maxx Orange

H317 May cause an allergic skin reaction

H351 Suspected of causing cancer (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard)

H336 May cause drowsiness or dizziness

Precautionary Statements:

P260 Do not breathe dust/fume/gas/mist/vapors/spray

P264 Wash hands thoroughly after handling

P280 Wear protective gloves/protective clothing/eye protection/face protection

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P272 Contaminated work clothing must not be allowed out of the workplace

P201 Obtain special instructions before use

P202 Do not handle until all safety precautions have been read and understood

P271 Use only outdoors or in a well-ventilated area

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

P363 Wash contaminated clothing before reuse

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

P310 Immediately call a POISON CENTER/doctor/...

P321 Specific treatment (see ... on this label)

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P302+P352 IF ON SKIN: Wash with plenty of water/ ...

P333+P313 If skin irritation or rash occurs: Get medical advice/attention

P308+P313 IF exposed or concerned: Get medical advice/attention

P312 Call a POISON CENTER/doctor/.../if you feel unwell

P405 Store locked up

P403+P233 Store in a well-ventilated place. Keep container tightly closed

P501 It is the responsibility of the waste generator to characterize all waste materials according to applicable regulatory entities.

Hazards Not Otherwise Classified: None

SECTION 3: Composition/Information on Ingredients

Identification	Name	Weight %
CAS Number: 68584-22-5	Benzenesulfonic acid, C10-16-alkyl derivatives	<50
CAS Number: 57-55-6	Propane-1,2-diol	<20
CAS Number: 5064-31-3	Trisodium nitrilotriacetate	<15
CAS Number: 111-76-2	2-Butoxyethanol	<8
CAS Number: 52-51-7	Bronopol (INN) 2-bromo-2-nitropropane-1,3-diol	<2
CAS Number: 26172-55-4	5-Chloro-2-methyl-4-isothiazolin-3-one	<1.5

Page 2 of 16

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 02.08.2024

Revision date: 02.08.2024

Power Maxx Orange

CAS Number: Ethane-1.2-diol < 0.0072 107-21-1

Additional Information: None

SECTION 4: First Aid Measures

Description of First Aid Measures

General Notes:

Show this Safety Data Sheet to the doctor in attendance.

After Inhalation:

If inhaled, remove person to fresh air and place in a position comfortable for breathing. Keep person at rest. If breathing is difficult, administer oxygen. If breathing has stopped, provide artificial respiration. If experiencing respiratory symptoms, seek medical advice/attention.

If inhaled, remove person to fresh air and place in a position comfortable for breathing. Keep person at rest. If breathing is difficult, administer oxygen. If breathing has stopped, provide artificial respiration. If symptoms develop or persist, seek medical advice/attention.

After Skin Contact:

Treatment is urgent. Seek emergency medical treatment. Remove contaminated clothing and shoes. Rinse skin with copious amounts of water [shower] for several minutes. Launder contaminated clothing before reuse.

Remove contaminated clothing and shoes. Rinse skin with copious amounts of water [shower] for several minutes. Launder contaminated clothing before reuse. If symptoms develop or persist, seek medical advice/attention.

After Eve Contact:

Immediately rinse eyes with plenty of gently flowing lukewarm water for 15 minutes. Remove contact lenses if present and easy to do so. Protect unexposed eye. Seek immediate medical attention, preferably from an ophthalmologist.

Rinse eyes with plenty of water for several minutes. Remove contact lenses if present and easy to do so. Protect unexposed eye. If symptoms develop or persist, seek medical advice/attention.

After Swallowing:

If swallowed, DO NOT induce vomiting unless told to do so by a physician or poison control center. Rinse mouth with water. Never give anything by mouth to an unconscious person. If spontaneous vomiting occurs, place on the left side with head down to prevent aspiration of liquid into the lungs. Seek immediate medical attention.

If swallowed, DO NOT induce vomiting unless told to do so by a physician or poison control center. Rinse mouth with water. Never give anything by mouth to an unconscious person. If spontaneous vomiting occurs, place on the left side with head down to prevent aspiration of liquid into the lungs. If symptoms develop or persist, seek medical advice/attention.

Most Important Symptoms and Effects, Both Acute and Delayed

Acute Symptoms and Effects:

Exposure to skin may result in redness, pain, burning, inflammation and tissue damage. Exposure to eyes may result in irritation, redness, pain, inflammation, itching, burning, tearing, corneal damage and loss of vision. Exposure via inhalation may result in cough, sore throat, burning sensation and shortness of breath. Exposure via ingestion may result in burns of the mouth and throat, abdominal pain, burning sensation in the throat and chest, nausea, vomiting, shock or collapse.

Eye contact may result in irritation, redness, pain, inflammation, itching, burning, tearing, corneal damage and loss of vision.

Dermal exposure may cause an allergic skin reaction. Symptoms may include irritation, redness, pain,

Page 3 of 16

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 02.08.2024

Revision date: 02.08.2024

Power Maxx Orange

rash, inflammation, itching, burning and dermatitis.

Inhalation may have adverse effects on the central nervous system. Symptoms may include drowsiness, dizziness, headache, nausea and lowering of consciousness. Acute overexposure via inhalation may result in respiratory distress, confusion and unconsciousness.

Delayed Symptoms and Effects:

Effects are dependent on exposure (dose, concentration, contact time).

Suspected of causing cancer. Effects are dependent on exposure (dose, concentration, contact time).

Immediate Medical Attention and Special Treatment

Specific Treatment:

In case of eye contact, seek prompt medical attention while rinsing is continued.

In case of skin contact, seek prompt medical attention while rinsing is continued.

In case of ingestion, seek prompt medical attention.

Overexposure via inhalation requires urgent medical treatment.

Notes for the Doctor:

Treat symptomatically.

SECTION 5: Firefighting Measures

Extinguishing Media

Suitable Extinguishing Media:

Water mist/fog, carbon dioxide, dry chemical or alcohol resistant foam.

Unsuitable Extinguishing Media:

Do not use water jet.

Specific Hazards During Fire-Fighting:

Thermal decomposition may produce irritating/toxic fumes/gases.

Special Protective Equipment for Firefighters:

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full-face piece operated in positive pressure mode.

Special precautions:

Avoid contact with skin, eyes, hair and clothing. Do not breathe fumes/gas/mists/aerosols/vapors/dusts. Move containers from fire area if safe to do so. Use water spray/fog for cooling fire exposed containers. Avoid unnecessary run-off of extinguishing media which may cause pollution.

SECTION 6: Accidental Release Measures

Personal Precautions, Protective Equipment, and Emergency Procedures:

Evacuate unnecessary personnel. Ventilate area. Extinguish any sources of ignition. Wear recommended personal protective equipment (see Section 8). Avoid contact with skin, eyes and clothing. Avoid breathing mist, vapor, dust, fume and spray. Do not walk through spilled material. Wash thoroughly after handling. Evacuate unnecessary personnel. Ventilate area. Extinguish any sources of ignition. Wear recommended personal protective equipment (see Section 8). Do not get on skin, eyes or on clothing. Avoid breathing mist, vapor, dust, fume and spray. Do not walk through spilled material. Wash thoroughly after handling. Remove contaminated clothing and launder before reuse.

Environmental Precautions:

Prevent further leakage or spillage if safe to do so. Prevent from reaching drains, sewers and waterways. Discharge into the environment must be avoided.

Methods and Material for Containment and Cleaning Up:

Page 4 of 16

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 02.08.2024

Revision date: 02.08.2024

Power Maxx Orange

Do not touch damaged containers or spilled material unless wearing appropriate personal protective clothing. Stop leak if you can do it without risk. Contain and collect spillage and place in suitable container for future disposal. Dispose of in accordance with all applicable regulations (see Section 13).

Do not touch damaged containers or spilled material unless wearing appropriate personal protective clothing. Avoid breathing dust, mist, fumes, vapors or spray. Stop leak if you can do it without risk. Contain and collect spillage and place in suitable container for future disposal. Dispose of in accordance with all applicable regulations (see Section 13).

Reference to Other Sections:

For personal protective equipment see Section 8. For disposal see Section 13.

SECTION 7: Handling and Storage

Precautions for Safe Handling:

Use appropriate personal protective equipment (see Section 8). Prevent skin contact. Do not get in eyes. Use only with adequate ventilation. Do not add water to the corrosive product. If it is necessary to mix a corrosive product with water, do so slowly adding the corrosive to cold water, in small amounts, and stir frequently. Avoid breathing mist/vapor/spray/dust. Do not eat, drink, smoke, or use personal products when handling chemical substances. Wash affected areas thoroughly after handling. Keep away from incompatible materials (See Section 10). Keep containers tightly closed when not in use. Keep only in original packaging. Use appropriate personal protective equipment (see Section 8). Use only with adequate ventilation. Avoid breathing mist/vapor/spray/dust. Do not eat, drink, smoke, or use personal products when handling chemical substances. Do not get in eyes. Avoid contact with skin and clothing. Wash affected areas thoroughly after handling. Keep away from incompatible materials (See Section 10). Keep containers tightly closed when not in use.

Use appropriate personal protective equipment (see Section 8). Use only with adequate ventilation. Avoid breathing mist/vapor/spray/dust. Do not eat, drink, smoke, or use personal products when handling chemical substances. Avoid contact with skin, eyes and clothing. Wash affected areas thoroughly after handling. Keep away from incompatible materials (See Section 10). Keep containers tightly closed when not in use.

Conditions for Safe Storage, Including Any Incompatibilities:

Store in cool, dry, well-ventilated location out of direct sunlight and away from exit paths. Store in a corrosion-resistant container with a resistant inner liner. Inspect containers and storage area regularly for signs of leak and damage. Store containers at a convenient height for handling, below eye level if possible. High shelving increases the risk of dropping containers, personal injury and exposure. Ensure that appropriate fire fighting and spill-clean up equipment is readily available. Keep away from food and beverages. Protect from freezing and physical damage. Store away from heat, open flames and other sources of ignition. Store separately. Keep container tightly sealed. Store away from incompatible materials (See Section 10).

Store in cool, dry, well-ventilated location out of direct sunlight. Keep away from food and beverages. Protect from freezing and physical damage. Store away from heat, open flames and other sources of ignition. Keep container tightly sealed. Store away from incompatible materials (See Section 10).

SECTION 8: Exposure Controls/Personal Protection

Only those substances with limit values have been included below.

Occupational Exposure Limit Values:

Occupational E	occupational Exposure Ellint Values.			
Country (Legal Basis)	Substance	Identifier	Permissible concentration	
ACGIH	Ethane-1,2-diol		8-Hour TWA: 25 ppm (vapor fraction)	

Page 5 of 16

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 02.08.2024 Page 6 of 16

Revision date: 02.08.2024

Power Maxx Orange

Country (Legal Basis)	Substance	Identifier	Permissible concentration
	Ethane-1,2-diol	107-21-1	15-Minute STEL: 50 ppm (vapor fraction)
	Ethane-1,2-diol	107-21-1	15-Minute STEL: 10 mg/m³ (aerosol only, inhalable fraction)
	2-Butoxyethanol	111-76-2	8-Hour TWA: 20 ppm
OSHA	2-Butoxyethanol	111-76-2	8-Hour TWA-PEL: 240 mg/m ³ (50 ppm)
	5-Chloro-2-methyl-4-isothiazolin-3-one	26172-55-4	MAK TWA: 0.2 mg/m ³
NIOSH	2-Butoxyethanol	111-76-2	IDLH: 700 ppm
	2-Butoxyethanol	111-76-2	REL-TWA: 24 mg/m³ (5 ppm [up to 10 hr])
United States(California)	2-Butoxyethanol	111-76-2	8-Hour TWA-PEL: 97 mg/m ³ (20 ppm)
	Ethane-1,2-diol	107-21-1	Ceiling Limit: 100 mg/m³ (40 ppm)
United States	2-Butoxyethanol	111-76-2	8-Hour TWA: 120 mg/m³ (25 ppm [U.S. State, Tennessee])
WEEL	Propane-1,2-diol	57-55-6	TWA: 10 mg/m³

Biological Limit Values:

Country (Legal Basis)	Substance		Determin ant	Specimen	Sampling time	Permissibl e limits
ACGIH	2-Butoxyethanol		, ,	Creatinine in Urine	End of shift	200 mg/g

Information on Monitoring Procedures:

Not determined or not applicable.

Appropriate Engineering Controls:

Emergency eye wash stations and safety showers should be available in the immediate vicinity of use or handling. Provide adequate ventilation to maintain the airborne concentrations of vapor, mists, and/or dusts below the applicable workplace exposure limits, while observing recognized national standards (or equivalent).

Personal Protection Equipment

Eye and Face Protection:

Use safety glasses with side shields or goggles. Consider the use of a face shield for splash protection. Use eye protection equipment that has been tested and approved by recognized national standards (or

Safety glasses or goggles. Use eye protection equipment that has been tested and approved by recognized national standards (or equivalent).

Skin and Body Protection:

Chemical resistant, impervious gloves approved by the appropriate standards. Gloves must be inspected prior to use. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. Avoid skin contact with used gloves. Appropriate techniques should be used to remove used gloves and

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 02.08.2024

Revision date: 02.08.2024

Power Maxx Orange

contaminated clothing. Full body protection should be worn. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Ensure that all personal protective equipment is approved by recognized national standards (or equivalent).

Chemical resistant, impervious gloves approved by the appropriate standards. Gloves must be inspected prior to use. Avoid skin contact with used gloves. Appropriate techniques should be used to remove used gloves and contaminated clothing. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Ensure that all personal protective equipment is approved by recognized national standards (or equivalent).

Respiratory Protection:

If engineering controls do not maintain airborne concentrations below the applicable workplace exposure limits, or to an acceptable level (if exposure limits have not been established), a respirator approved by recognized national standards (or equivalent) must be worn.

If engineering controls do not maintain airborne concentrations below the applicable workplace exposure limits, or to an acceptable level (if exposure limits have not been established), a respirator approved by recognized national standards (or equivalent) must be worn. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.

General Hygienic Measures:

When handling chemical products, do not eat, drink or smoke. Wash hands after handling, before breaks, and at the end of the workday. Avoid contact with skin, eyes and clothing. Wash contaminated clothing before reuse. Perform routine housekeeping.

SECTION 9: Physical and Chemical Properties

Information on Basic Physical and Chemical Properties

Appearance	Not determined or not available.
Odor	Not determined or not available.
Odor threshold	Not determined or not available.
рН	Not determined or not available.
Melting point/freezing point	Not determined or not available.
Initial boiling point/range	Not determined or not available.
Flash point (closed cup)	Not determined or not available.
Evaporation rate	Not determined or not available.
Flammability (solid, gas)	Not determined or not available.
Upper flammability/explosive limit	Not determined or not available.
Lower flammability/explosive limit	Not determined or not available.
Vapor pressure	Not determined or not available.
Vapor density	Not determined or not available.
Density	Not determined or not available.
Relative density	Not determined or not available.
Solubilities	Not determined or not available.
Partition coefficient (n-octanol/water)	Not determined or not available.
Auto/Self-ignition temperature	Not determined or not available.
Decomposition temperature	Not determined or not available.
	L

Page 7 of 16

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 02.08.2024

Revision date: 02.08.2024

Power Maxx Orange

Dynamic viscosity	Not determined or not available.	
Kinematic viscosity	Not determined or not available.	
Explosive properties	Not determined or not available.	
Oxidizing properties	Not determined or not available.	

SECTION 10: Stability and Reactivity

Reactivity:

Not reactive under recommended handling and storage conditions.

Chemical Stability:

Stable under recommended handling and storage conditions.

Possibility of Hazardous Reactions:

Hazardous reactions are not anticipated under recommended conditions of handling and storage.

Conditions to Avoid:

Avoid generation of aerosols and mists, extreme heat, open flames, hot surfaces, sparks, ignition sources and incompatible materials.

Extreme heat, open flames, hot surfaces, sparks, ignition sources and incompatible materials.

Incompatible Materials:

None known.

Hazardous Decomposition Products:

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological Information

Acute Toxicity

Assessment: Based on available data, the classification criteria are not met.

Product Data: No data available.

Substance Data:

Name	Route	Result
Trisodium nitrilotriacetate	oral	LD50 Rat: 1100 mg/kg
	dermal	LD50 Rabbit: >2000 mg/kg
	inhalation	LC50 Rat: >5 mg/L (4 hr - Aerosol)
Benzenesulfonic acid, C10-16-	inhalation	LC50 Rat: >1.9 mg/L (4 h [aerosol])
alkyl derivatives	Dermal ATE	LD50 Rabbit: 1100 mg/kg
	Oral ATE	LD50 Rat: 500 mg/kg
Bronopol (INN) 2-bromo-2-	dermal	LD50 Rat: 1600 mg/kg
nitropropane-1,3-diol	oral	LD50 Rat: 193 mg/kg
	inhalation	LC50 Rat: > 0.588 mg/L (4 hr [aerosol])
Ethane-1,2-diol	dermal	LD50 Mouse: > 3500 mg/kg
	Oral ATE	LD50 Rat: 500 mg/kg (Converted acute toxicity point estimate)
	inhalation	LC50 Rat: >2.5 mg/L (6 hr [Aerosol])
2-Butoxyethanol	Dermal ATE	LD50 Rabbit: 1100 mg/kg
	Oral ATE	LD50 Rat: 1200 mg/kg
	Inhalation ATE	LC50 Rat: 3 mg/L (4 hr [Vapours])

Page 8 of 16

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 02.08.2024

Revision date: 02.08.2024

Power Maxx Orange

Name	Route	Result
Propane-1,2-diol	oral	LD50 Rat: 22,000 mg/kg
	dermal	LD50 Rabbit: >2000 mg/kg
	inhalation	LC50 Rabbit: > 44.9 mg/L (4hr [vapour])
5-Chloro-2-methyl-4-	oral	LD50 Rat: 53 mg/kg
isothiazolin-3-one	dermal	LD50 Rat: 113 mg/kg
	inhalation	LC50 Rat: 0.33 mg/L (4 hr [aerosol])

Skin Corrosion/Irritation

Assessment:

Causes severe skin burns and eye damage.

Product Data:

No data available.

Substance Data:

Name	Result
Benzenesulfonic acid, C10-16-alkyl derivatives	Causes severe skins burns.
Bronopol (INN) 2-bromo-2- nitropropane-1,3-diol	Causes skin irritation.
5-Chloro-2-methyl-4- isothiazolin-3-one	Causes severe skin burns.
2-Butoxyethanol	Causes skin irritation.

Serious Eye Damage/Irritation

Assessment:

Causes serious eye damage.

Product Data:

No data available.

Substance Data:

Name	Result
Trisodium nitrilotriacetate	Causes serious eye irritation.
Benzenesulfonic acid, C10-16-alkyl derivatives	Causes serious eye damage.
Bronopol (INN) 2-bromo-2- nitropropane-1,3-diol	Causes serious eye damage.
5-Chloro-2-methyl-4- isothiazolin-3-one	Causes serious eye damage.
2-Butoxyethanol	Causes serious eye irritation.

Respiratory or Skin Sensitization

Assessment:

May cause an allergic skin reaction.

Product Data:

No data available.

Substance Data:

Page 9 of 16

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 02.08.2024

Revision date: 02.08.2024

Power Maxx Orange

Name	Result
5-Chloro-2-methyl-4-	May cause an allergic skin reaction.
isothiazolin-3-one	May cause respiratory irritation.

Carcinogenicity

Assessment:

Suspected of causing cancer. **Product Data:** No data available.

Substance Data:

Name	Species	Result
Trisodium nitrilotriacetate		Suspected of causing cancer.

International Agency for Research on Cancer (IARC):

Name	Classification
Ethane-1,2-diol	Not Applicable
Trisodium nitrilotriacetate	Group 2B
Benzenesulfonic acid, C10-16-alkyl derivatives	Not Applicable
2-Butoxyethanol	Group 3
5-Chloro-2-methyl-4- isothiazolin-3-one	Not Applicable
Propane-1,2-diol	Not Applicable
Bronopol (INN) 2-bromo-2- nitropropane-1,3-diol	Not Applicable

National Toxicology Program (NTP):

Name	Classification
Ethane-1,2-diol	Not Applicable
Trisodium nitrilotriacetate	Not Applicable
Benzenesulfonic acid, C10-16- alkyl derivatives	Not Applicable
2-Butoxyethanol	Not Applicable
5-Chloro-2-methyl-4- isothiazolin-3-one	Not Applicable
Propane-1,2-diol	Not Applicable
Bronopol (INN) 2-bromo-2- nitropropane-1,3-diol	Not Applicable

OSHA Carcinogens: Not applicable

Germ Cell Mutagenicity

Assessment: Based on available data, the classification criteria are not met.

Product Data:No data available.

Substance Data: No data available.

Reproductive Toxicity

Assessment: Based on available data, the classification criteria are not met.

Product Data:

Page 10 of 16

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 02.08.2024

Revision date: 02.08.2024

Power Maxx Orange

No data available.

Substance Data: No data available.

Specific Target Organ Toxicity (Single Exposure)

Assessment:

May cause drowsiness or dizziness.

Product Data: No data available. Substance Data:

Name	Result
Bronopol (INN) 2-bromo-2- nitropropane-1,3-diol	May cause respiratory irritation.

Specific Target Organ Toxicity (Repeated Exposure)

Assessment: Based on available data, the classification criteria are not met.

Product Data:
No data available.
Substance Data:

Name	Result
Ethane-1,2-diol	May cause damage to Kidney through prolonged or repeated oral
	exposure.

Aspiration toxicity

Assessment: Based on available data, the classification criteria are not met.

Product Data:No data available.

Substance Data: No data available.

Information on Likely Routes of Exposure:

No data available.

Symptoms Related to the Physical, Chemical, and Toxicological Characteristics:

No data available. **Other Information:**No data available.

SECTION 12: Ecological Information

Acute (Short-Term) Toxicity

Assessment: Based on available data, the classification criteria are not met.

Product Data: No data available.

Substance Data:

Name	Result
	Aquatic Invertebrates EC50 Daphnia magna: 1.4 mg/L (48 hr [mobility])
nitropropane-1,3-diol	Fish LC50 Lepomis macrochirus: 11 mg/L (96 hr)
	Aquatic Plants EC50 Desmodesmus subspicatus: 0.026 mg/L (72 hr [growth rate])

Page 11 of 16

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Page 12 of 16

Initial Preparation Date: 02.08.2024

Revision date: 02.08.2024

Power Maxx Orange

Name	Result
5-Chloro-2-methyl-4- isothiazolin-3-one	Fish LC50 Oncorhynchus mykiss: 0.19 mg/L (96 hr)
	Aquatic Invertebrates EC50 Daphnia magna: 0.18 mg/L (48 hr [intoxication & immobility]ata])
	Aquatic Plants EC50 Skeletonema costatum: 0.021 mg/L (96 hr [population, abundance])
Ethane-1,2-diol	Aquatic Plants EC50 Raphidocelis subcapitata: 6500 - 13,000 mg/L (96 hr [growth rate])
	Aquatic Invertebrates EC50 Daphnia magna: > 100 mg/L (48 hr)
	Fish LC50 Pimephales promelas: 72,860 mg/L (96 hr)
2-Butoxyethanol	Aquatic Invertebrates EC50 Daphnia magna: 1550 mg/L (48 hr [mobility])
	Fish LC50 Oncorhynchus mykiss: 1474 mg/L (96 hr)
	Aquatic Plants EC50 Raphidocelis subcapitata: 623 mg/L (72 hr [biomass])
Propane-1,2-diol	Fish LC50 Oncorhynchus mykiss: 51,600 mg/L (96 hr)
	Aquatic Plants EC50 Raphidocelis subcapitata: 19000 mg/L (96 hr [growth rate])
	Aquatic Invertebrates EC50 Daphnia magna: 43,500 mg/L (48 hr [Immobilisation])
Trisodium nitrilotriacetate	Fish LC50 Pimephales promelas: 114 mg/L (96 hr)
	Aquatic Plants EC50 Desmodesmus subspicatus: >100 mg/L (72 hr [growth rate])
	Aquatic Invertebrates EC50 Daphnia magna: 560 mg/L (96 hr [mortality])
Benzenesulfonic acid, C10-16-alkyl derivatives	Aquatic Invertebrates EC50 Daphnia magna: >1000 mg/L (48hr [mobility] Read-across)
	Aquatic Plants EC50 Raphidocelis subcapitata: >1000 mg/L (72 hr [growth rate] Read-across)

Chronic (Long-Term) Toxicity

Assessment: Based on available data, the classification criteria are not met.

Product Data: No data available.

Substance Data:

Name	Result
	Fish NOEC Menidia peninsulae: > 40 mg/L (28 d [mortality])
	Aquatic Invertebrates NOEC Daphnia magna: > 15,000 mg/L mg/L (21 d [reproduction])
2-Butoxyethanol	Fish NOEC Danio rerio: > 100 mg/L (21 d [markers for endocrine disruptive effects])
	Aquatic Invertebrates NOEC Daphnia magna: 100 mg/L (21 d [reproduction])
Trisodium nitrilotriacetate	Aquatic Invertebrates LC50 Pagurus longicarpus: 1875 mg/L (7 d)
Propane-1,2-diol	Aquatic Invertebrates NOEC Ceriodaphnia sp.: 13020 mg/L (7 d [reproduction])
Bronopol (INN) 2-bromo-2- nitropropane-1,3-diol	Fish NOEC Oncorhynchus mykiss: 2.61 mg/L (28 d [mortality])
	Aquatic Invertebrates NOEC Daphnia magna: 0.27 mg/L (21 d [appearance of first brood, Immobility, number of unhatched eggs])

Persistence and Degradability

Product Data: No data available.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 02.08.2024 **Revision date:** 02.08.2024

Power Maxx Orange

Substance Data:

substance Data.	
Name	Result
Benzenesulfonic acid, C10-16-alkyl derivatives	Under test conditions no biodegradation observed.
Bronopol (INN) 2-bromo-2- nitropropane-1,3-diol	The substance is readily biodegradable. 70 - 80% degradation in water, measured by CO2 evolution, after 28 days.
Ethane-1,2-diol	The substance is Readily biodegradable. 90-100% degradation in water, measured by DOC removal, after 10 days.
Trisodium nitrilotriacetate	Substance is readily biodegradable. >95% degradation in water, measured by DOC removal, after 28 days.
2-Butoxyethanol	The substance is readily biodegradable. 90.4% degradation, measured by CO2 evolution, after 28 days.
5-Chloro-2-methyl-4- isothiazolin-3-one	The substance is inherently biodegradable. 62% degradation in water, measured by CO2 evolution, after 28 days.
Propane-1,2-diol	The substance is readily biodegradable. 81.7% degradation in water,

Bioaccumulative Potential

Product Data: No data available.

Substance Data:

Name	Result
Ethane-1,2-diol	The substance is not expected to bioaccumulate (log Pow=: -1.93).
2-Butoxyethanol	The substance is not expected to bioaccumulate (log Kow = 0.83).
Trisodium nitrilotriacetate	Bioaccumulation is not expected. BCF (aquatic species): 3 L/kg ww
Propane-1,2-diol	The substance is not expected to bioaccumulate (BCF: 0.09).
Bronopol (INN) 2-bromo-2- nitropropane-1,3-diol	The substance is not expected to bioaccumulate (BCF=3.9 L/kg basis-whole body w.w., QSAR substance data).

measured by CO2 evolution, after 28 days.

Mobility in Soil

Product Data: No data available.

Substance Data:

Jubstance Data.	
Name	Result
Ethane-1,2-diol	Adsorption to the solid soil phase is not expected.
Trisodium nitrilotriacetate	The substance has a low potential for adsorption to soil and sediment. log Kp (sediment-water): 1.6 L/kg
5-Chloro-2-methyl-4- isothiazolin-3-one	The substance is mobile to moderately mobile, therefore, slight adsorption to soil is expected (Koc= 30-144).
Propane-1,2-diol	The substance is highly mobile, therefore, adosrption to soil is not expected (calculated Koc: 2.9).
Bronopol (INN) 2-bromo-2- nitropropane-1,3-diol	The substance is highly mobile; therefore, adsorption to soil is not expected (Koc= 1 L/kg at 25 °C, QSAR substance data).

Results of PBT and vPvB assessment

Product Data:

PBT assessment: This product does not contain any substances that are assessed to be a PBT. **vPvB assessment:** This product does not contain any substances that are assessed to be a vPvB.

Substance Data:

PBT assessment:

Trisodium nitrilotriacetate	The substance is not PBT.
-----------------------------	---------------------------

Page 13 of 16

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 02.08.2024

Revision date: 02.08.2024

Power Maxx Orange

vPvB assessment:	
Bronopol (INN) 2-bromo-2- nitropropane-1,3-diol	The substance is not PBT.
Propane-1,2-diol	The substance is not PBT.
2-Butoxyethanol	The substance is not PBT.
Ethane-1,2-diol	The substance is not PBT.

Trisodium nitrilotriacetate	The substance is not vPvB.
Ethane-1,2-diol	The substance is not vPvB.
2-Butoxyethanol	The substance is not vPvB.
Propane-1,2-diol	The substance is not vPvB.
Bronopol (INN) 2-bromo-2- nitropropane-1,3-diol	The substance is not vPvB.

Other Adverse Effects: No data available.

SECTION 13: Disposal Considerations

Disposal Methods:

It is the responsibility of the waste generator to properly characterize all waste materials according to applicable regulatory entities

Contaminated packages:

Not determined or not applicable.

SECTION 14: Transport Information

United States Transportation of Dangerous Goods (49 CFR DOT)

UN Number	Not Regulated
UN Proper Shipping Name	Not regulated
UN Transport Hazard Class(es)	None
Packing Group	None
Environmental Hazards	None
Special Precautions for User	None

International Maritime Dangerous Goods (IMDG)

UN Number	Not regulated
UN Proper Shipping Name	Not regulated
UN Transport Hazard Class(es)	None
Packing Group	None
Environmental Hazards	None
Special Precautions for User	None

International Air Transport Association Dangerous Goods Regulations (IATA-DGR)

UN Number	Not regulated
UN Proper Shipping Name	Not regulated
UN Transport Hazard Class(es)	None
Packing Group	None

Page 14 of 16

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 02.08.2024

Revision date: 02.08.2024

Power Maxx Orange

02.08.2024			
range			

Page 15 of 16

Environmental Hazards	None
Special Precautions for User	None

SECTION 15: Regulatory Information

United States Regulations

Inventory Listing (TSCA): All ingredients are listed-active or exempt.

Significant New Use Rule (TSCA Section 5):

68584-22-5	Benzenesulfonic acid, C10-16-alkyl derivatives	Not Listed
107-21-1	Ethane-1,2-diol	Not Listed
5064-31-3	Trisodium nitrilotriacetate	Not Listed
111-76-2	2-Butoxyethanol	Not Listed
26172-55-4	5-Chloro-2-methyl-4-isothiazolin-3-one	Listed
57-55-6	Propane-1,2-diol	Not Listed
52-51-7	Bronopol (INN) 2-bromo-2-nitropropane-1,3-diol	Not Listed

Export Notification under TSCA Section 12(b):

68584-22-5	Benzenesulfonic acid, C10-16-alkyl derivatives	Not Listed
107-21-1	Ethane-1,2-diol	Not Listed
111-76-2	2-Butoxyethanol	Not Listed
5064-31-3	Trisodium nitrilotriacetate	Not Listed
26172-55-4	5-Chloro-2-methyl-4-isothiazolin-3-one	Listed
57-55-6	Propane-1,2-diol	Not Listed
52-51-7	Bronopol (INN) 2-bromo-2-nitropropane-1,3-diol	Not Listed

SARA Section 302 Extremely Hazardous Substances: None of the ingredients are listed.

SARA Section 313 Toxic Chemicals:

107-21-1	Ethane-1,2-diol	Listed
111-76-2	2-Butoxyethanol	Listed
5064-31-3	Trisodium nitrilotriacetate	Listed

CERCLA:

107-21-1	Ethane-1,2-diol	Listed	5000 lbs
- h	2-Butoxyethanol	Listed	N/A

RCRA: None of the ingredients are listed.

Section 112(r) of the Clean Air Act (CAA):

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 02.08.2024 Page 16 of 16

Revision date: 02.08.2024

Power Maxx Orange

107-21-1	Ethane-1,2-diol	Listed		
Massachusetts R	ight to Know:	,		
107-21-1	Ethane-1,2-diol	Listed		
5064-31-3	Trisodium nitrilotriacetate	Listed		
111-76-2	2-Butoxyethanol	Listed		
New Jersey Right	to Know:			
107-21-1	Ethane-1,2-diol	Listed		
111-76-2	2-Butoxyethanol	Listed		
57-55-6	Propane-1,2-diol	Listed		
New York Right t	o Know:	•		
107-21-1	Ethane-1,2-diol	Listed		
111-76-2	2-Butoxyethanol	Listed		
Pennsylvania Rig	ennsylvania Right to Know:			
107-21-1	Ethane-1,2-diol	Listed		
111-76-2	2-Butoxyethanol	Listed		
57-55-6	Propane-1,2-diol	Listed		

California Proposition 65:

▲WARNING: This product can expose you to Ethane-1,2-diol; which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Additional information: Not determined.

SECTION 16: Other Information

Abbreviations and Acronyms: None

Disclaimer:

This product has been classified in accordance with OSHA HCS 2012 guidelines. The information provided in this SDS is correct, to the best of our knowledge, based on information available. The information given is designed only as a guidance for safe handling, use, storage, transportation and disposal and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials, unless specified in the text. The responsibility to provide a safe workplace remains with the user.

NFPA: 0-0-0 **HMIS:** 0-0-0

Initial Preparation Date: 02.08.2024

Revision date: 02.08.2024

End of Safety Data Sheet