

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

**Initial Preparation Date: 05.14.2019** 

**Revision date: 02.08.2024** 

#### Wild Tire and Wheel Cleaner

#### **SECTION 1: Identification**

**Product Identifier** 

Product Name: Wild Tire and Wheel Cleaner

Product code: C-1124

Recommended Use of the Product and Restriction on Use

Relevant Identified Uses: Wheel and Tire Cleaner, Foaming Detergent

Uses Advised Against: NA

Reasons Why Uses Advised Against: Not determined or not applicable.

#### **Manufacturer or Supplier Details**

Manufacturer: **United States** 

**Heiden Industries** 1200 Veterans Blvd. Kenner, LA. 70062 8008784913 TODD@HEIDENIND.COM

#### **Emergency Telephone Number:**

**North America** 

CHEMTREC 800-424-9300 (24 hours)

#### SECTION 2: Hazard(s) Identification

#### **GHS Classification:**

Skin corrosion, category 1A Serious eye damage, category 1 Carcinogenicity, category 2 Specific target organ toxicity - repeated exposure, category 2

#### **Label elements**

#### **Hazard Pictograms:**





# Signal Word: Danger **Hazard statements:**

H314 Causes severe skin burns and eye damage

H318 Causes serious eye damage

H351 Suspected of causing cancer.

H373 May cause damage to organs.

#### **Precautionary Statements:**

Page 1 of 19

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 05.14.2019

**Revision date: 02.08.2024** 

#### **Wild Tire and Wheel Cleaner**

P260 Do not breathe dust/fume/gas/mist/vapors/spray

P280 Wear protective gloves/protective clothing/eye protection/face protection

P202 Do not handle until all safety precautions have been read and understood

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

P363 Wash contaminated clothing before reuse

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P308+P313 IF exposed or concerned: Get medical advice/attention

P314 Get medical advice/attention if you feel unwell

P405 Store locked up

P501 It is the responsibility of the waste generator to characterize all waste materials according to applicable regulatory entities.

Hazards Not Otherwise Classified: None

## SECTION 3: Composition/Information on Ingredients

Identification	Name	Weight %
CAS Number: 527-07-1	Sodium gluconate	1-10
CAS Number: Proprietary	Cationic/Nonionic Surfactant Blend	1-10
CAS Number: 1310-58-3	Potassium hydroxide	1-10
CAS Number: 68515-73-1	D-Glucopyranose, oligomers, decyl octyl glycosides	1-10
CAS Number: 7758-29-4	Pentasodium triphosphate	1-10
CAS Number: 111-76-2	2-Butoxyethanol	<10
CAS Number: 64-02-8	Tetrasodium ethylenediamine tetraacetate	1-5
CAS Number: 61789-40-0	1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-, N-coco acyl derivs., hydroxides, inner salts	<10
CAS Number: 1310-73-2	Sodium hydroxide	1-5
CAS Number: 50-00-0	Formaldehyde	<0.018
CAS Number: 79-43-6	Dichloroacetic acid	<0.009
CAS Number: 107-21-1	Ethane-1,2-diol	<0.009

Page 2 of 19

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

**Initial Preparation Date:** 05.14.2019

**Revision date:** 02.08.2024

Wild Tire and Wheel Cleaner

Additional Information: None

#### **SECTION 4: First Aid Measures**

#### **Description of First Aid Measures**

#### **General Notes:**

Not determined or not applicable.

#### **After Inhalation:**

If inhaled, remove person to fresh air and place in a position comfortable for breathing. Keep person at rest. If breathing is difficult, administer oxygen. If breathing has stopped, provide artificial respiration. If symptoms develop or persist, seek medical advice/attention.

If inhaled, remove person to fresh air and place in a position comfortable for breathing. Keep person at rest. If breathing is difficult, administer oxygen. If breathing has stopped, provide artificial respiration. If experiencing respiratory symptoms, seek medical advice/attention.

#### **After Skin Contact:**

Treatment is urgent. Seek emergency medical treatment. Remove contaminated clothing and shoes. Rinse skin with copious amounts of water [shower] for several minutes. Launder contaminated clothing before reuse.

Remove contaminated clothing and shoes. Rinse skin with copious amounts of water [shower] for several minutes. Launder contaminated clothing before reuse. If symptoms develop or persist, seek medical advice/attention.

#### **After Eye Contact:**

Immediately rinse eyes with plenty of gently flowing lukewarm water for 15 minutes. Remove contact lenses if present and easy to do so. Protect unexposed eye. Seek immediate medical attention, preferably from an ophthalmologist.

Rinse eyes with plenty of water for several minutes. Remove contact lenses if present and easy to do so. Protect unexposed eye. If symptoms develop or persist, seek medical advice/attention.

#### **After Swallowing:**

If Swallowed, DO NOT induce vomiting unless directed otherwise by a medical professional. Rinse mouth with water. Never give anything to an unconscious person. Seek medical attention.

If swallowed, DO NOT induce vomiting unless told to do so by a physician or poison control center. Rinse mouth with water. Never give anything by mouth to an unconscious person. If spontaneous vomiting occurs, place on the left side with head down to prevent aspiration of liquid into the lungs. Seek immediate medical attention.

If swallowed, DO NOT induce vomiting unless told to do so by a physician or poison control center. Rinse mouth with water. Never give anything by mouth to an unconscious person. If spontaneous vomiting occurs, place on the left side with head down to prevent aspiration of liquid into the lungs. If symptoms develop or persist, seek medical advice/attention.

# Most Important Symptoms and Effects, Both Acute and Delayed Acute Symptoms and Effects:

Exposure to skin may result in redness, pain, burning, inflammation and tissue damage. Exposure to eyes may result in irritation, redness, pain, inflammation, itching, burning, tearing, corneal damage and loss of vision. Exposure via inhalation may result in cough, sore throat, burning sensation and shortness of breath. Exposure via ingestion may result in burns of the mouth and throat, abdominal pain, burning sensation in the throat and chest, nausea, vomiting, shock or collapse.

Eye contact may result in irritation, redness, pain, inflammation, itching, burning, tearing, corneal damage and loss of vision.

#### **Delayed Symptoms and Effects:**

Page 3 of 19

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 05.14.2019 Page

**Revision date: 02.08.2024** 

#### Wild Tire and Wheel Cleaner

Effects are dependent on exposure (dose, concentration, contact time).

Suspected of causing cancer. Effects are dependent on exposure (dose, concentration, contact time).

May cause damage to organs through prolonged or repeated exposure. Effects are dependent on exposure (dose, concentration, contact time).

## **Immediate Medical Attention and Special Treatment**

#### **Specific Treatment:**

In case of eye contact, seek prompt medical attention while rinsing is continued.

In case of skin contact, seek prompt medical attention while rinsing is continued.

In case of ingestion, seek prompt medical attention.

#### **Notes for the Doctor:**

Not determined or not applicable.

## **SECTION 5: Firefighting Measures**

#### **Extinguishing Media**

#### **Suitable Extinguishing Media:**

Water mist/fog, carbon dioxide, dry chemical or alcohol resistant foam.

#### **Unsuitable Extinguishing Media:**

Do not use water jet.

#### **Specific Hazards During Fire-Fighting:**

Thermal decomposition may produce irritating/toxic fumes/gases.

#### Special Protective Equipment for Firefighters:

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full-face piece operated in positive pressure mode.

#### **Special precautions:**

Avoid contact with skin, eyes, hair and clothing. Do not breathe fumes/gas/mists/aerosols/vapors/dusts. Move containers from fire area if safe to do so. Use water spray/fog for cooling fire exposed containers. Avoid unnecessary run-off of extinguishing media which may cause pollution.

#### **SECTION 6: Accidental Release Measures**

#### Personal Precautions, Protective Equipment, and Emergency Procedures:

Evacuate unnecessary personnel. Ventilate area. Extinguish any sources of ignition. Wear recommended personal protective equipment (see Section 8). Avoid contact with skin, eyes and clothing. Avoid breathing mist, vapor, dust, fume and spray. Do not walk through spilled material. Wash thoroughly after handling. Evacuate unnecessary personnel. Ventilate area. Extinguish any sources of ignition. Wear recommended personal protective equipment (see Section 8). Do not get on skin, eyes or on clothing. Avoid breathing mist, vapor, dust, fume and spray. Do not walk through spilled material. Wash thoroughly after handling. Remove contaminated clothing and launder before reuse.

#### **Environmental Precautions:**

Prevent further leakage or spillage if safe to do so. Prevent from reaching drains, sewers and waterways. Discharge into the environment must be avoided.

#### Methods and Material for Containment and Cleaning Up:

Do not touch damaged containers or spilled material unless wearing appropriate personal protective clothing. Stop leak if you can do it without risk. Contain and collect spillage and place in suitable container for future disposal. Dispose of in accordance with all applicable regulations (see Section 13).

Do not touch damaged containers or spilled material unless wearing appropriate personal protective clothing. Avoid breathing dust, mist, fumes, vapors or spray. Stop leak if you can do it without risk. Contain

Page 4 of 19

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

**Initial Preparation Date: 05.14.2019** 

**Revision date: 02.08.2024** 

#### Wild Tire and Wheel Cleaner

and collect spillage and place in suitable container for future disposal. Dispose of in accordance with all applicable regulations (see Section 13).

#### **Reference to Other Sections:**

For personal protective equipment see Section 8. For disposal see Section 13.

### **SECTION 7: Handling and Storage**

#### Precautions for Safe Handling:

Use appropriate personal protective equipment (see Section 8). Prevent skin contact. Do not get in eyes. Use only with adequate ventilation. Do not add water to the corrosive product. If it is necessary to mix a corrosive product with water, do so slowly adding the corrosive to cold water, in small amounts, and stir frequently. Avoid breathing mist/vapor/spray/dust. Do not eat, drink, smoke, or use personal products when handling chemical substances. Wash affected areas thoroughly after handling. Keep away from incompatible materials (See Section 10). Keep containers tightly closed when not in use. Keep only in original packaging. Use appropriate personal protective equipment (see Section 8). Use only with adequate ventilation. Avoid breathing mist/vapor/spray/dust. Do not eat, drink, smoke, or use personal products when handling chemical substances. Do not get in eyes. Avoid contact with skin and clothing. Wash affected areas thoroughly after handling. Keep away from incompatible materials (See Section 10). Keep containers tightly closed when not in use.

Use appropriate personal protective equipment (see Section 8). Use only with adequate ventilation. Avoid breathing mist/vapor/spray/dust. Do not eat, drink, smoke, or use personal products when handling chemical substances. Avoid contact with skin, eyes and clothing. Wash affected areas thoroughly after handling. Keep away from incompatible materials (See Section 10). Keep containers tightly closed when not

#### Conditions for Safe Storage, Including Any Incompatibilities:

Store in cool, dry, well-ventilated location out of direct sunlight and away from exit paths. Store in a corrosion-resistant container with a resistant inner liner. Inspect containers and storage area regularly for signs of leak and damage. Store containers at a convenient height for handling, below eye level if possible. High shelving increases the risk of dropping containers, personal injury and exposure. Ensure that appropriate fire fighting and spill-clean up equipment is readily available. Keep away from food and beverages. Protect from freezing and physical damage. Store away from heat, open flames and other sources of ignition. Store separately. Keep container tightly sealed. Store away from incompatible materials (See Section 10).

Store in cool, dry, well-ventilated location out of direct sunlight. Keep away from food and beverages. Protect from freezing and physical damage. Store away from heat, open flames and other sources of ignition. Keep container tightly sealed. Store away from incompatible materials (See Section 10). Store in cool and dry location and out of direct sunlight. Store away from sources of heat or ignition. Store away from incompatible materials described in Section 10. Keep containers closed when not in use. Keep away from food and beverages. Protect from freezing and physical damage.

#### SECTION 8: Exposure Controls/Personal Protection

Only those substances with limit values have been included below.

#### Occupational Exposure Limit Values:

Country (Legal Basis)	Substance	Identifier	Permissible concentration
WEEL	Cationic/Nonionic Surfactant Blend	Proprietary	TWA: 10 mg/m³ (Aerosol)
ACGIH	Potassium hydroxide	1310-58-3	Ceiling Limit: 2 mg/m <sup>3</sup>
	Sodium hydroxide	1310-73-2	Ceiling Limit: 2 mg/m³
	2-Butoxyethanol	111-76-2	8-Hour TWA: 20 ppm

Page 5 of 19

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Page 6 of 19

Initial Preparation Date: 05.14.2019

**Revision date:** 02.08.2024

# Wild Tire and Wheel Cleaner

Country (Legal Basis)	Substance	Identifier	Permissible concentration
	Formaldehyde	50-00-0	15-Minute STEL: 0.3 ppm
	Formaldehyde	50-00-0	TLV-TWA: 0.1 ppm (8 hr)
	Dichloroacetic acid	79-43-6	8-Hour TWA: 0.5 ppm
	Ethane-1,2-diol	107-21-1	8-Hour TWA: 25 ppm (vapor fraction)
	Ethane-1,2-diol	107-21-1	15-Minute STEL: 50 ppm (vapor fraction)
	Ethane-1,2-diol	107-21-1	15-Minute STEL: 10 mg/m³ (aerosol only, inhalable fraction)
NIOSH	Potassium hydroxide	1310-58-3	Ceiling Limit: 2 mg/m³
	Sodium hydroxide	1310-73-2	IDLH: 10 mg/m³
	2-Butoxyethanol	111-76-2	IDLH: 700 ppm
	2-Butoxyethanol	111-76-2	REL-TWA: 24 mg/m³ (5 ppm [up to 10 hr])
	Sodium hydroxide	1310-73-2	Ceiling Limit: 2 mg/m <sup>3</sup>
	Formaldehyde	50-00-0	IDLH: 20 ppm
	Formaldehyde	50-00-0	Ceiling Limit: 0.1 ppm ([15-min])
	Formaldehyde	50-00-0	REL: 0.016 ppm ([for up to a 10-hour workday)
OSHA	Sodium hydroxide	1310-73-2	8-Hour TWA-PEL: 2 mg/m <sup>3</sup>
	2-Butoxyethanol	111-76-2	8-Hour TWA-PEL: 240 mg/m <sup>3</sup> (50 ppm)
	Formaldehyde	50-00-0	STEL: 2 ppm
	Formaldehyde	50-00-0	TWA: 0.75 ppm
United States(California)	Potassium hydroxide	1310-58-3	Ceiling Limit: 2 mg/m³
	Sodium hydroxide	1310-73-2	Ceiling Limit: 2 mg/m³
	Sodium hydroxide	1310-73-2	REL: 8 ug/m³ (Acute Inhalation)
	2-Butoxyethanol	111-76-2	8-Hour TWA-PEL: 97 mg/m <sup>3</sup> (20 ppm)
	Formaldehyde	50-00-0	15-Minute STEL: 2 ppm
	Formaldehyde	50-00-0	8-Hour TWA-PEL: 0.75 ppm
	Formaldehyde	50-00-0	REL: 55 ug/m³ (Acute Inhalation)
	Formaldehyde	50-00-0	REL: 9 ug/m³ (Chronic Inhalation)
	Ethane-1,2-diol	107-21-1	Ceiling Limit: 100 mg/m³ (40 ppm)
United States	2-Butoxyethanol	111-76-2	8-Hour TWA: 120 mg/m³ (25 ppm [U.S. State, Tennessee])

# **Biological Limit Values:**

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

**Initial Preparation Date: 05.14.2019** Page 7 of 19

**Revision date: 02.08.2024** 

#### Wild Tire and Wheel Cleaner

Country (Legal Basis)	Substance	Determin ant	Specimen		Permissibl e limits
ACGIH	2-Butoxyethanol	,	Creatinine in Urine	End of shift	200 mg/g

#### Information on Monitoring Procedures:

Not determined or not applicable.

#### **Appropriate Engineering Controls:**

Emergency eye wash stations and safety showers should be available in the immediate vicinity of use or handling. Provide adequate ventilation to maintain the airborne concentrations of vapor, mists, and/or dusts below the applicable workplace exposure limits, while observing recognized national standards (or equivalent).

#### **Personal Protection Equipment**

#### **Eye and Face Protection:**

Use safety glasses with side shields or goggles. Consider the use of a face shield for splash protection. Use eye protection equipment that has been tested and approved by recognized national standards (or

Safety glasses or goggles. Use eye protection equipment that has been tested and approved by recognized national standards (or equivalent).

#### **Skin and Body Protection:**

Chemical resistant, impervious gloves approved by the appropriate standards. Gloves must be inspected prior to use. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. Avoid skin contact with used gloves. Appropriate techniques should be used to remove used gloves and contaminated clothing. Full body protection should be worn. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Ensure that all personal protective equipment is approved by recognized national standards (or equivalent).

Chemical resistant, impervious gloves approved by the appropriate standards. Gloves must be inspected prior to use. Avoid skin contact with used gloves. Appropriate techniques should be used to remove used gloves and contaminated clothing. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Ensure that all personal protective equipment is approved by recognized national standards (or equivalent).

#### **Respiratory Protection:**

If engineering controls do not maintain airborne concentrations below the applicable workplace exposure limits, or to an acceptable level (if exposure limits have not been established), a respirator approved by recognized national standards (or equivalent) must be worn.

If engineering controls do not maintain airborne concentrations below the applicable workplace exposure limits, or to an acceptable level (if exposure limits have not been established), a respirator approved by recognized national standards (or equivalent) must be worn. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.

#### **General Hygienic Measures:**

When handling chemical products, do not eat, drink or smoke. Wash hands after handling, before breaks, and at the end of the workday. Avoid contact with skin, eyes and clothing. Wash contaminated clothing

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 05.14.2019

**Revision date: 02.08.2024** 

#### **Wild Tire and Wheel Cleaner**

before reuse. Perform routine housekeeping.

#### SECTION 9: Physical and Chemical Properties

#### **Information on Basic Physical and Chemical Properties**

Appearance	Liquid
Odor	Std.
Odor threshold	Not determined or not available.
рН	14
Melting point/freezing point	Not determined or not available.
Initial boiling point/range	Not determined or not available.
Flash point (closed cup)	Not determined or not available.
Evaporation rate	Not determined or not available.
Flammability (solid, gas)	Not determined or not available.
Upper flammability/explosive limit	Not determined or not available.
Lower flammability/explosive limit	Not determined or not available.
Vapor pressure	Not determined or not available.
Vapor density	Not determined or not available.
Density	Not determined or not available.
Relative density	Not determined or not available.
Solubilities	Not determined or not available.
Partition coefficient (n-octanol/water)	Not determined or not available.
Auto/Self-ignition temperature	Not determined or not available.
Decomposition temperature	Not determined or not available.
Dynamic viscosity	Not determined or not available.
Kinematic viscosity	Not determined or not available.
Explosive properties	Not determined or not available.
Oxidizing properties	Not determined or not available.

# SECTION 10: Stability and Reactivity

#### Reactivity:

Not reactive under recommended handling and storage conditions.

# **Chemical Stability:**

Stable under recommended handling and storage conditions.

#### **Possibility of Hazardous Reactions:**

Hazardous reactions are not anticipated under recommended conditions of handling and storage.

#### **Conditions to Avoid:**

Avoid generation of aerosols and mists, extreme heat, open flames, hot surfaces, sparks, ignition sources and incompatible materials.

Extreme heat, open flames, hot surfaces, sparks, ignition sources and incompatible materials.

## **Incompatible Materials:**

None known.

#### **Hazardous Decomposition Products:**

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Page 8 of 19

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 05.14.2019

**Revision date: 02.08.2024** 

**Wild Tire and Wheel Cleaner** 

# SECTION 11: Toxicological Information

#### **Acute Toxicity**

**Assessment:** Based on available data, the classification criteria are not met.

**Product Data:** No data available.

**Substance Data:** 

Name	Route	Result
Potassium hydroxide	oral	LD50 Rat: 333 mg/kg
Tetrasodium ethylenediamine	oral	LD50 Rat: 1780 mg/kg
tetraacetate	Inhalation ATE	LC50 Rat: 1.5 mg/L (4 hr [Aerosol])
2-Butoxyethanol	Dermal ATE	LD50 Rabbit: 1100 mg/kg
	Oral ATE	LD50 Rat: 1200 mg/kg
	Inhalation ATE	LC50 Rat: 3 mg/L (4 hr [Vapours])
D-Glucopyranose, oligomers,	oral	LD50 Rat: > 2000 mg/kg
decyl octyl glycosides	dermal	LD50 Rabbit: > 2000 mg/kg
Pentasodium triphosphate	oral	LD50 Rat: >2000 mg/kg
	dermal	LD50 Rabbit: > 4640 mg/kg
	inhalation	LC50 Rat: 0.39 mg/L (4 hr [Aerosol])
Sodium hydroxide	Oral ATE	LD50 Rat: 500 mg/kg
	dermal	LD50 Rabbit: 1350 mg/kg
1-Propanaminium, 3-amino-N- (carboxymethyl)-N,N-dimethyl-,		LD50 Rat: > 5000 mg/kg
N-coco acyl derivs., hydroxides, inner salts	dermal	LD50 Rat: > 2000 mg/kg
Formaldehyde	oral	LD50 Rat: 100 mg/kg
	inhalation	LC50 Rat: 3 mg/L (4 hr [vapor])
	dermal	LD50 Rat: 300 mg/kg
Dichloroacetic acid	dermal	LD50 Rabbit: 797 mg/kg
	oral	LD50 Rat: 2820 mg/kg
Ethane-1,2-diol	dermal	LD50 Mouse: > 3500 mg/kg
	Oral ATE	LD50 Rat: 500 mg/kg (Converted acute toxicity point estimate)
	inhalation	LC50 Rat: >2.5 mg/L (6 hr [Aerosol])

#### **Skin Corrosion/Irritation**

#### **Assessment:**

Causes severe skin burns and eye damage.

#### **Product Data:**

No data available.

#### **Substance Data:**

Name	Result
Potassium hydroxide	Causes severe skin burns.
Sodium hydroxide	Causes severe skin burns.

Page 9 of 19

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 05.14.2019 Page 1

**Revision date: 02.08.2024** 

#### **Wild Tire and Wheel Cleaner**

Name	Result
1-Propanaminium, 3-amino-N- (carboxymethyl)-N,N-dimethyl-, N-coco acyl derivs., hydroxides, inner salts	
2-Butoxyethanol	Causes skin irritation.
Formaldehyde	Causes severe skin burns.
Dichloroacetic acid	Causes severe skin burns.

#### **Serious Eye Damage/Irritation**

#### **Assessment:**

Causes serious eye damage.

# **Product Data:**

No data available.

#### **Substance Data:**

Name	Result
Potassium hydroxide	Causes serious eye damage.
D-Glucopyranose, oligomers, decyl octyl glycosides	Causes serious eye damage.
Sodium hydroxide	Causes serious eye damage.
Tetrasodium ethylenediamine tetraacetate	Causes serious eye damage.
1-Propanaminium, 3-amino-N- (carboxymethyl)-N,N-dimethyl-, N-coco acyl derivs., hydroxides, inner salts	
2-Butoxyethanol	Causes serious eye irritation.
Formaldehyde	Causes serious eye damage.
Dichloroacetic acid	Causes serious eye damage.

# Respiratory or Skin Sensitization

**Assessment:** Based on available data, the classification criteria are not met.

**Product Data:**No data available.

<b>Substance</b>	Data:
------------------	-------

Name	Result
1-Propanaminium, 3-amino-N- (carboxymethyl)-N,N-dimethyl-, N-coco acyl derivs., hydroxides, inner salts	
Formaldehyde	May cause an allergic skin reaction.

# Carcinogenicity

#### **Assessment:**

Suspected of causing cancer. **Product Data:** No data available.

**Substance Data:** 

Page 10 of 19

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 05.14.2019 Page

**Revision date:** 02.08.2024

# **Wild Tire and Wheel Cleaner**

Name	Species	Result
Formaldehyde		May cause cancer.
Dichloroacetic acid		Suspected of causing cancer.

# International Agency for Research on Cancer (IARC):

Name	Classification
Sodium gluconate	Not Applicable
Potassium hydroxide	Not Applicable
D-Glucopyranose, oligomers, decyl octyl glycosides	Not Applicable
Pentasodium triphosphate	Not Applicable
Sodium hydroxide	Not Applicable
Tetrasodium ethylenediamine tetraacetate	Not Applicable
1-Propanaminium, 3-amino-N- (carboxymethyl)-N,N-dimethyl-, N-coco acyl derivs., hydroxides, inner salts	Not Applicable
2-Butoxyethanol	Group 3
Formaldehyde	Group 1
Dichloroacetic acid	Group 2B
Ethane-1,2-diol	Not Applicable

# **National Toxicology Program (NTP):**

Name	Classification
Sodium gluconate	Not Applicable
Potassium hydroxide	Not Applicable
D-Glucopyranose, oligomers, decyl octyl glycosides	Not Applicable
Pentasodium triphosphate	Not Applicable
Sodium hydroxide	Not Applicable
Tetrasodium ethylenediamine tetraacetate	Not Applicable
1-Propanaminium, 3-amino-N- (carboxymethyl)-N,N-dimethyl-, N-coco acyl derivs., hydroxides, inner salts	
2-Butoxyethanol	Not Applicable
Formaldehyde	Known to be human carcinogens
Dichloroacetic acid	Reasonably anticipated to be human carcinogens
Ethane-1,2-diol	Not Applicable

# **OSHA Carcinogens:**

Ingredient Name	CAS	OSHA Carcinogens Status
Formaldehyde	50-00-0	Yes

# **Germ Cell Mutagenicity**

Page 11 of 19

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 05.14.2019

**Revision date: 02.08.2024** 

#### **Wild Tire and Wheel Cleaner**

**Assessment:** Based on available data, the classification criteria are not met.

**Product Data:**No data available. **Substance Data:** 

Name	Result
Formaldehyde	Suspected of causing genetic defects.

#### **Reproductive Toxicity**

**Assessment:** Based on available data, the classification criteria are not met.

Product Data: No data available. Substance Data:

Name	Result
Dichloroacetic acid	May damage fertility or the unborn child.
	May cause harm to breast-fed children.

## **Specific Target Organ Toxicity (Single Exposure)**

**Assessment:** Based on available data, the classification criteria are not met.

**Product Data:**No data available. **Substance Data:** 

Name	Result
Formaldehyde	May cause respiratory irritation.

#### **Specific Target Organ Toxicity (Repeated Exposure)**

#### **Assessment:**

May cause damage to organs through prolonged or repeated exposure.

#### **Product Data:**

No data available.

#### **Substance Data:**

Name	Result
Tetrasodium ethylenediamine tetraacetate	Animal studies indicate that chronic exposure can cause damage to organs. Causes changes in tubules (including acute renal failure and necrosis) in intraperitoneal lethal-dose studies of mice; [RTECS]
Dichloroacetic acid	May cause damage to organs (brain, liver, testes) through prolonged or repeated exposure
Ethane-1,2-diol	May cause damage to Kidney through prolonged or repeated oral exposure.

## Aspiration toxicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product Data:**No data available.

Substance Data: No data available.

#### Information on Likely Routes of Exposure:

No data available.

## Symptoms Related to the Physical, Chemical, and Toxicological Characteristics:

No data available.

Page 12 of 19

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 05.14.2019

**Revision date:** 02.08.2024

#### **Wild Tire and Wheel Cleaner**

## Other Information:

No data available.

# SECTION 12: Ecological Information

#### Acute (Short-Term) Toxicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product Data:** No data available.

**Substance Data:** 

Name	Result
2-Butoxyethanol	Aquatic Invertebrates EC50 Daphnia magna: 1550 mg/L (48 hr [mobility])
	Fish LC50 Oncorhynchus mykiss: 1474 mg/L (96 hr)
	Aquatic Plants EC50 Raphidocelis subcapitata: 623 mg/L (72 hr [biomass])
D-Glucopyranose, oligomers,	Fish LC50 Danio rerio: 100.81 mg/L (96 hr)
decyl octyl glycosides	Aquatic Invertebrates EC50 Daphnia magna: > 100 mg/L (48 hr [mobility])
	Aquatic Plants EC50 Desmodesmus subspicatus: 27.22 mg/L (72 hr [growth rate])
Pentasodium triphosphate	Fish LC50 Danio rerio: >1850 mg/L (24 hr)
	Aquatic Invertebrates EC50 Daphnia magna: >100 mg/L (48 hr [immobilisation])
Sodium hydroxide	Aquatic Invertebrates EC50 Ceriodaphnia sp.: 40.4 mg/L (48 hr [immobilization])
	Fish LC50 Fish: 35 - 189 mg/L (96 hr)
Tetrasodium ethylenediamine	Fish LC50 Oncorhynchus mykiss: >100 mg/L (96 hr)
tetraacetate	Aquatic Invertebrates EC50 Daphnia magna: 140 mg/L (48 hr [mobility])
	Aquatic Plants EC50 Pseudokirchneriella subcapitata: >60 mg/L (72 hr [growth rate])
1-Propanaminium, 3-amino-N-	Fish LC50 Danio rerio: 2 mg/L (96 hr)
(carboxymethyl)-N,N-dimethyl-, N-coco acyl derivs., hydroxides,	Aquatic Invertebrates EC50 Daphnia magna: 6.4 mg/L (48 hr [mobility])
inner salts	Aquatic Plants EC50 Ulva lactuca: 30 mg/L (48 hr [biomass])
Formaldehyde	Fish LC50 Morone saxatilis: 6.7 mg/L (96 hr)
	Aquatic Invertebrates EC50 Daphnia pulex: 5.8 mg/L (48 hr [mobility])
	Aquatic Plants EC50 Desmodesmus subspicatus: 3.48 mg/L (72 hr [biomass])
Dichloroacetic acid	Fish LC50 Marine water fish: >2000 mg/L (96 h)
	Aquatic Plants EC50 Marine water algae: 148.2 mg/L (72 h [cell number])
Ethane-1,2-diol	Aquatic Plants EC50 Raphidocelis subcapitata: 6500 - 13,000 mg/L (96 hr [growth rate])
	Aquatic Invertebrates EC50 Daphnia magna: > 100 mg/L (48 hr)
	Fish LC50 Pimephales promelas: 72,860 mg/L (96 hr)

# **Chronic (Long-Term) Toxicity**

**Assessment:** Based on available data, the classification criteria are not met.

Product Data: No data available.

**Substance Data:** 

Page 13 of 19

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 05.14.2019

**Revision date:** 02.08.2024

# **Wild Tire and Wheel Cleaner**

Name	Result
lala avil a atvil alluga a i da a	Fish NOEC Danio rerio: 1.8 mg/L (28 d [read-across])
	Aquatic Invertebrates NOEC Daphnia magna: 2 mg/L (21 d [read-across])
Tetrasodium ethylenediamine	Fish NOEC Danio rerio: >=35.1 mg/L (35 d)
tetraacetate	Aquatic Invertebrates NOEC Daphnia magna: 25 mg/L (21 d [reproduction])
1-Propanaminium, 3-amino-N- (carboxymethyl)-N,N-dimethyl-, N-coco acyl derivs., hydroxides, inner salts	
2-Butoxyethanol	Fish NOEC Danio rerio: > 100 mg/L (21 d [markers for endocrine disruptive effects])
	Aquatic Invertebrates NOEC Daphnia magna: 100 mg/L (21 d [reproduction])
Formaldehyde	Aquatic Invertebrates NOEC Daphnia magna: 1.04 mg/L (21 d)
	Fish LC50 Danio rerio: 6.9 mg/L (6 d)
Ethane-1,2-diol	Fish NOEC Menidia peninsulae: > 40 mg/L (28 d [mortality])
	Aquatic Invertebrates NOEC Daphnia magna: > 15,000 mg/L mg/L (21 d [reproduction])

# **Persistence and Degradability**

**Product Data:** No data available.

#### **Substance Data:**

Name	Result
D-Glucopyranose, oligomers, decyl octyl glycosides	The substance is readily biodegradable in water. 100% degradation, measured by DOC removal, after 28 days.
Potassium hydroxide	The study on degradability does not need to be conducted as the substance is inorganic.
Pentasodium triphosphate	Persistence assessment based on biodegradability is not relevant for inorganic compounds such as this substance.
Sodium hydroxide	Persistence assessment based on biodegradability is not relevant for inorganic compounds such as this substance.
Tetrasodium ethylenediamine tetraacetate	The substance is not readily biodegradable. 76% degradation, measured by O2 consumption, after 56 days.
1-Propanaminium, 3-amino-N- (carboxymethyl)-N,N-dimethyl-, N-coco acyl derivs., hydroxides, inner salts	The substance is readily biodegradable. > 90% degradation (test mat. analysis), after 5 days.
2-Butoxyethanol	The substance is readily biodegradable. 90.4% degradation, measured by CO2 evolution, after 28 days.
Formaldehyde	Substance is readily biodegradable 99% degradation measured by DOC removal after 28 days.
Dichloroacetic acid	The substance is readily biodegradable. 93% degradation, measured by Oxygen consumption, after 15 days.
Ethane-1,2-diol	The substance is Readily biodegradable. 90-100% degradation in water, measured by DOC removal, after 10 days.

#### **Bioaccumulative Potential**

**Product Data:** No data available.

Page 14 of 19

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 05.14.2019

**Revision date: 02.08.2024** 

**Wild Tire and Wheel Cleaner** 

#### **Substance Data:**

Name	Result
Tetrasodium ethylenediamine tetraacetate	This substance is not expected to bioaccumulate. BCF (aquatic species): 1.8 L/kg
1-Propanaminium, 3-amino-N- (carboxymethyl)-N,N-dimethyl-, N-coco acyl derivs., hydroxides, inner salts	
Potassium hydroxide	Not expected to bioaccumulate, as it completely dissociates in water.
Pentasodium triphosphate	Bioaccumulation assessment using a classic BCF assessment is not considered relevant for inorganic compounds such as this substance.
Sodium hydroxide	Bioaccumulation assessment using a classic BCF assessment is not considered relevant for inorganic compounds such as this substance.
2-Butoxyethanol	The substance is not expected to bioaccumulate (log Kow = $0.83$ ).
Formaldehyde	Accumulation in aquatic organisms is not to be expected [BCF (aquatic species): 0.396 dimensionless].
Dichloroacetic acid	This substance has low potential for bioaccumulation.
Ethane-1,2-diol	The substance is not expected to bioaccumulate (log Pow=: -1.93).

# **Mobility in Soil**

**Product Data:** No data available.

#### **Substance Data:**

Name	Result
Tetrasodium ethylenediamine tetraacetate	This substance is expected to be moderately mobile with a moderate potential for adsorption to soil and sediment. Calculated Koc: 312.7 dimensionless.
1	The substance is mobile to moderately mobile (experimental log Koc: 1.812 dimensionless; calculated Koc: 648 L/kg); therefore, moderate adsorption to soil can be expected.
Potassium hydroxide	Low potential for adsorption. If emitted to surface water, sorption to sediment will be negligible.
D-Glucopyranose, oligomers, decyl octyl glycosides	Substance is expected to be mobile (log Koc: 1.7); therefore, adsorption to soil is not expected.
Pentasodium triphosphate	The substance is moderately mobile, therefore, slight adsorption to soil is expected (log Koc=2.15)
Sodium hydroxide	Mobility in soil assessment based on KOC/Kd values are not relevant for inorganic compounds such as this substance.
Formaldehyde	Adsorption to solid soil phase is possible. [Koc at 20 °C: 15.9]
Dichloroacetic acid	This substance will not adsorb at all to soils or sediments should these environmental compartments be exposed to it.
Ethane-1,2-diol	Adsorption to the solid soil phase is not expected.

#### **Results of PBT and vPvB assessment**

# **Product Data:**

**PBT assessment:** This product does not contain any substances that are assessed to be a PBT. **vPvB assessment:** This product does not contain any substances that are assessed to be a vPvB.

# Substance Data: PBT assessment:

Page 15 of 19

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

**Initial Preparation Date:** 05.14.2019 Page 16 of 19

**Revision date: 02.08.2024** 

#### **Wild Tire and Wheel Cleaner**

Potassium hydroxide	The substance is not PBT.
D-Glucopyranose, oligomers, decyl octyl glycosides	The substance is not PBT.
Tetrasodium ethylenediamine tetraacetate	This substance is not PBT.
1-Propanaminium, 3-amino-N- (carboxymethyl)-N,N- dimethyl-, N-coco acyl derivs., hydroxides, inner salts	The substance is not PBT.
Pentasodium triphosphate	PBT assessment does not apply to inorganic compounds such as this substance.
Sodium hydroxide	PBT assessment does not apply to inorganic compounds such as this substance.
2-Butoxyethanol	The substance is not PBT.
Formaldehyde	Not a PBT substance.
Dichloroacetic acid	The substance is not PBT.
Ethane-1,2-diol	The substance is not PBT.
VDVP passassments	

# vPvB assessment:

Potassium hydroxide	The substance is not vPvB.
D-Glucopyranose, oligomers, decyl octyl glycosides	The substance is not vPvB.
Tetrasodium ethylenediamine tetraacetate	This substance is not vPvB.
1-Propanaminium, 3-amino-N- (carboxymethyl)-N,N- dimethyl-, N-coco acyl derivs., hydroxides, inner salts	The substance is not vPvB.
Pentasodium triphosphate	vPvB assessment does not apply to inorganic compounds such as this substance.
Sodium hydroxide	vPvB assessment does not apply to inorganic compounds such as this substance.
2-Butoxyethanol	The substance is not vPvB.
Formaldehyde	Not a vPvB substance.
Dichloroacetic acid	The substance is not vPvB.
Ethane-1,2-diol	The substance is not vPvB.

Other Adverse Effects: No data available.

# **SECTION 13: Disposal Considerations**

#### **Disposal Methods:**

It is the responsibility of the waste generator to characterize all waste materials according to applicable regulatory entities.

#### Contaminated packages:

Not determined or not applicable.

# **SECTION 14: Transport Information**

United States Transportation of Dangerous Goods (49 CFR DOT)

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 05.14.2019

**Revision date: 02.08.2024** 

#### **Wild Tire and Wheel Cleaner**

UN Number	1814
UN Proper Shipping Name	Potassium Hydroxide, Solution
UN Transport Hazard Class(es)	8
Packing Group	II
Environmental Hazards	None
Special Precautions for User	None

#### **International Maritime Dangerous Goods (IMDG)**

UN Number	Not regulated
UN Proper Shipping Name	Not regulated
UN Transport Hazard Class(es)	None
Packing Group	None
Environmental Hazards	None
Special Precautions for User	None

### International Air Transport Association Dangerous Goods Regulations (IATA-DGR)

UN Number	Not regulated
UN Proper Shipping Name	Not regulated
UN Transport Hazard Class(es)	None
Packing Group	None
Environmental Hazards	None
Special Precautions for User	None

# **SECTION 15: Regulatory Information**

# **United States Regulations**

107-21-1

**Inventory Listing (TSCA):** All ingredients are listed-active or exempt.

**Significant New Use Rule (TSCA Section 5):** None of the ingredients are listed. **Export Notification under TSCA Section 12(b):** None of the ingredients are listed.

# **SARA Section 302 Extremely Hazardous Substances:**

Ethane-1,2-diol

50-00-0	Formaldehyde		Listed
SARA Section 31	3 Toxic Chemicals:		
111-76-2	2-Butoxyethanol		Listed
50-00-0	Formaldehyde		Listed
107-21-1	Ethane-1,2-diol	Ethane-1,2-diol	
CERCLA:			
1310-58-3	Potassium hydroxide	Listed	1000 lb
1310-73-2	Sodium hydroxide	Listed	1000 lb
111-76-2	2-Butoxyethanol	Listed	N/A
50-00-0	Formaldehyde	Listed	100 lb

Listed

5000 lbs

Page 17 of 19

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 05.14.2019 Page 18 of 19

**Revision date: 02.08.2024** 

50-00-0

#### **Wild Tire and Wheel Cleaner**

Sec	Section 112(r) of the Clean Air Act (CAA):		
	50-00-0	Formaldehyde	Listed
	107-21-1	Ethane-1,2-diol	Listed

Listed

U122

#### **Massachusetts Right to Know:**

Formaldehyde

1310-58-3	Potassium hydroxide	Listed
7758-29-4	Pentasodium triphosphate	Listed
1310-73-2	Sodium hydroxide	Listed
111-76-2	2-Butoxyethanol	Listed
50-00-0	Formaldehyde	Listed
107-21-1	Ethane-1,2-diol	Listed

#### **New Jersey Right to Know:**

1310-58-3	Potassium hydroxide	Listed
1310-73-2	Sodium hydroxide	Listed
111-76-2	2-Butoxyethanol	Listed
50-00-0	Formaldehyde	Listed
79-43-6	Dichloroacetic acid	Listed
107-21-1	Ethane-1,2-diol	Listed

#### New York Right to Know:

1310-58-3	Potassium hydroxide	Listed
7758-29-4	Pentasodium triphosphate	Listed
1310-73-2	Sodium hydroxide	Listed
111-76-2	2-Butoxyethanol	Listed
50-00-0	Formaldehyde	Listed
79-43-6	Dichloroacetic acid	Listed
107-21-1	Ethane-1,2-diol	Listed

#### **Pennsylvania Right to Know:**

1310-58-3	Potassium hydroxide	Listed
7758-29-4	Pentasodium triphosphate	Listed
1310-73-2	Sodium hydroxide	Listed
111-76-2	2-Butoxyethanol	Listed
50-00-0	Formaldehyde	Listed
107-21-1	Ethane-1,2-diol	Listed

## **California Proposition 65:**

▲ WARNING: This product can expose you to Formaldehyde; which is known to the State of California to cause cancer; and Ethane-1,2-diol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

▲WARNING: This product can expose you to Dichloroacetic acid; which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

**Additional information:** Not determined.

#### **SECTION 16: Other Information**

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial Preparation Date: 05.14.2019 Page 19 of 19

**Revision date: 02.08.2024** 

#### **Wild Tire and Wheel Cleaner**

#### Abbreviations and Acronyms: None

Disclaimer:

This product has been classified in accordance with OSHA HCS 2012 guidelines. The information provided in this SDS is correct, to the best of our knowledge, based on information available. The information given is designed only as a guidance for safe handling, use, storage, transportation and disposal and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials, unless specified in the text. The responsibility to provide a safe workplace remains with the user.

**NFPA:** 0-0-0 **HMIS:** 0-0-0

**Initial Preparation Date:** 05.14.2019

**Revision date:** 02.08.2024

**End of Safety Data Sheet**